

Unità condensatrici ad aria semiermetiche

Air-cooled semi-hermetic condensing units

Halbhermetische luftgekühlte Verflüssigungssätze

Codice Frigo System	Tipo Type Typ	Compressore Compressor Verdichter DORIN	Ventilatori - Fans - Lüfter			Ric.liq.-Liq.rec.-Samm- Volume Volume Volumen [dm ³]	Ingombri Dimensions Abmessungen			Connes.-Connect.-Anschl.	
			Nr.-No.-Anz	Φ	giri-RPM-		L	P	H	Aspirazione	Liquido
										Suction	Liquid
										Austritt	Flüssig
						[mm]	[mm]	[mm]		[mm]	[mm]

APPLICAZIONE - APPLICATION - ANWENDUNG T.N.

70AH48CC4P	UA-H48CC4P-FS	H40CC	2	300	1400	4,0	785	630	400	12	10
70AH48CC	UA-H48CC-FS		2	300	900	4,0	785	630	400	12	10
70AH78CC4P	UA-H78CC4P-FS	H75CC	2	300	1400	4,0	785	630	400	12	10
70AH78CC	UA-H78CC-FS		2	300	900	4,0	785	630	400	12	10
70AH108CC4P	UA-H108CC4P-FS	H100CC	2	300	1400	4,0	785	630	400	16	10
70AH108CC	UA-H108CC-FS		2	300	900	4,0	785	630	400	16	10
70AH158CC4P	UA-H158CC4P-FS	H150CC	2	300	1400	4,0	785	630	400	16	10
70AH158CC	UA-H158CC-FS		2	350	900	4,0	940	750	450	16	10
70AH188CC4P	UA-H188CC4P-FS	H180CC	2	300	1400	4,0	785	630	450	16	10
70AH188CC	UA-H188CC-FS		2	350	900	4,0	940	750	450	16	10
70AH208CC4P	UA-H208CC4P-FS	H200CC	2	350	1400	4,0	940	750	450	16	10
70AH208CC	UA-H208CC-FS		2	400	900	4,0	940	750	550	16	10
70AH228CC4P	UA-H228CC4P-FS	H220CC	2	350	1400	4,0	940	750	450	18	10
70AH228CC	UA-H228CC-FS		2	400	900	4,0	940	750	550	18	10
70AH258CC4P	UA-H258CC4P-FS	H250CC	2	350	1400	6,0	940	750	450	18	10
70AH258CC	UA-H258CC-FS		2	400	900	6,0	940	750	550	18	10
70AH288CC4P	UA-H288CC4P-FS	H280CC	2	400	1400	6,0	940	750	550	18	10
70AH288CC	UA-H288CC-FS		2	450	900	6,0	1190	860	600	18	10
70AH308CC4P	UA-H308CC4P-FS	H300CC	2	400	1400	6,0	940	750	550	22	16
70AH308CC	UA-H308CC-FS		2	450	900	6,0	1190	860	600	22	16
70AH358CC4P	UA-H358CC4P-FS	H350CC	2	450	1400	15,0	1190	860	600	28	16
70AH358CC	UA-H358CC-FS		2	450	900	15,0	1190	860	600	28	16
70AH388CC4P	UA-H388CC4P-FS	H380CC	2	450	1400	15,0	1190	860	600	28	16
70AH388CC	UA-H388CC-FS		2	450	900	15,0	1190	860	600	28	16
70AH408CC4P	UA-H408CC4P-FS	H403CC	2	450	1400	15,0	1190	860	600	28	16
70AH408CC	UA-H408CC-FS		2	500	900	15,0	1190	860	600	28	16
70AH508CC4P	UA-H508CC4P-FS	H503CC	2	500	1400	15,0	1190	860	600	28	16
70AH508CC	UA-H508CC-FS		2	560	900	15,0	1290	1000	850	28	16
70AH558CC4P	UA-H558CC4P-FS	H550CC	2	500	1400	15,0	1190	860	600	28	16
70AH558CC	UA-H558CC-FS		2	560	900	15,0	1290	1000	850	28	16
70AH748CC	UA-H748CC-FS	H743CC	2	560	900	15,0	1290	1000	850	35	16
70AH708CC	UA-H708CC-FS	H700CC	2	560	900	15,0	1290	1000	850	35	16
70AK758CC	UA-K758CC-FS	K750CC	2	560	900	20,0	1290	1000	1050	35	22
70AH758CC	UA-H758CC-FS	H750CC	2	560	900	20,0	1290	1000	1050	35	22
70AK1008CC	UA-K1008CC-FS	K1000CC	2	630	900	2 x 20,0	1600	1100	1100	35	22
70AK1508CC	UA-K1508CC-FS	K1500CC	2	630	900	2 x 20,0	2500	1200	1180	42	22
70AK2008CC	UA-K2008CC-FS	K2000CC	2	630	900	2 x 20,0	2500	1200	1180	42	22
70AKP2008CC	UA-KP2008CC-FS	KP2000CC	2	630	900	2 x 20,0	2500	1200	1180	42	22
70AK2508CC	UA-K2508CC-FS	K2500CC	2	630	900	2 x 20,0	2500	1200	1225	42	28
70AK3008CC	UA-K3008CC-FS	K3000CC	3	630	900	2 x 20,0	3600	1200	1225	54	28