



**Unità condensatrici semiermetiche con condensatore raffreddato ad acqua**  
**Semi-hermetic condenser units with water cooled condenser**  
**Halbhermetische kondensatoreinheiten mit wassergekühltem Kondensator**

Serie W: unità con condensatore verticale in controcorrente non ispezionabile

W series: units with vertical condenser in counter-flow and which cannot be inspected

Serie W: nicht wur insoextion geeignete Einheit mit Vertikalkondensator im Gregonstrom

**Unità condensatrici semiermetiche con condensatore raffreddato ad acqua**

**Semi-hermetic condenser units with water cooled condenser**

**Halbhermetische kondensatoreinheiten mit wassergekühltem Kondensator**

Codice Frigo System	Tipo Type Typ	Compress. Dorin Dorin Compress. Verdichter Dorin	Volume lato refrigerante Refrigerant side volume [dm <sup>3</sup> ]	Ingombri Dimensions Abmessungen			Connes. -Connec.-Anschl.		Valv. H <sub>2</sub> O
				L [mm]	P [mm]	H [mm]	Aspiraz. Suction Austritt	Liquido Liquid Flüssig	
							[mm]	[mm]	

APPLICAZIONE - APPLICATION - ANWENDUNG							T.N.		
70WH48CC	UW-H48CC-FS	H40CC	4,6	350	505	485	12	10	3/8"
70WH78CC	UW-H78CC-FS	H75CC	4,6	350	505	485	12	10	3/8"
70WH108CC	UW-H108CC-FS	H100CC	8,4	350	505	485	16	10	3/8"
70WH158CC	UW-H158CC-FS	H150CC	8,4	350	505	485	16	10	3/8"
70WH188CC	UW-H188CC-FS	H180CC	8,3	350	505	485	16	10	3/8"
70WH208CC	UW-H208CC-FS	H200CC	8,3	350	505	485	16	10	3/8"
70WH228CC	UW-H228CC-FS	H220CC	8,3	350	505	485	18	10	3/8"
70WH258CC	UW-H258CC-FS	H250CC	8,1	350	505	485	18	12	1/2"
70WH288CC	UW-H288CC-FS	H280CC	8,1	350	505	485	18	12	1/2"
70WH308CC	UW-H308CC-FS	H300CC	19,3	470	550	605	22	12	1/2"
70WH358CC	UW-H358CC-FS	H350CC	19,3	470	550	605	28	16	3/4"
70WH388CC	UW-H388CC-FS	H380CC	19,3	470	550	605	28	16	3/4"
70WH408CC	UW-H408CC-FS	H403CC	19,3	675	720	605	28	16	3/4"
70WH508CC	UW-H508CC-FS	H503CC	19,0	675	720	605	28	16	3/4"
70WH558CC	UW-H558CC-FS	H550CC	19,0	675	720	605	28	16	3/4"
70WH748CC	UW-H748CC-FS	H743CC	20,1	675	720	655	35	18	1"
70WH708CC	UW-H708CC-FS	H700CC	20,1	675	720	655	35	18	1"
70WK758CC	UW-K758CC-FS	K750CC	20,1	675	720	655	35	18	1"
70WH758CC	UW-H758CC-FS	H750CC	20,1	675	720	655	35	18	1"

APPLICAZIONE - APPLICATION - ANWENDUNG							B.T.		
70WH59CS	UW-H59CS-FS	H50CS	4,6	350	505	485	12	10	3/8"
70WH79CS	UW-H79CS-FS	H75CS	4,6	350	505	485	16	10	3/8"
70WH109CS	UW-H109CS-FS	H100CS	4,6	350	505	485	16	10	3/8"
70WH159CS	UW-H159CS-FS	H150CS	8,4	350	505	485	16	10	3/8"
70WH189CS	UW-H189CS-FS	H180CS	8,4	350	505	485	16	10	3/8"
70WH209CS	UW-H209CS-FS	H200CS	8,4	350	505	485	18	10	3/8"
70WH229CS	UW-H229CS-FS	H220CS	8,3	350	505	485	18	10	3/8"
70WH259CS	UW-H259CS-FS	H250CS	8,3	350	505	485	18	12	3/8"
70WH299CS	UW-H299CS-FS	H290CS	8,3	350	505	485	22	12	3/8"
70WH309CS	UW-H309CS-FS	H300CS	8,3	470	550	600	28	12	3/8"
70WH359SB	UW-H359SB-FS	H350SB	8,1	470	550	600	28	12	1/2"
70WH389SB	UW-H389SB-FS	H380SB	8,1	470	550	600	28	16	1/2"
70WH399CS	UW-H399CS-FS	H390CS	8,1	470	550	600	28	16	1/2"
70WH392CS	UW-H392CS-FS	H392CS	19,3	675	720	605	28	16	1/2"
70WH409CS	UW-H409CS-FS	H403CS	19,3	675	720	605	28	16	1/2"
70WH459CS	UW-H459CS-FS	H450CS	19,3	675	720	605	28	16	3/4"
70WH509CS	UW-H509CS-FS	H503CS	19,3	675	720	605	35	16	3/4"
70WH559CS	UW-H559CS-FS	H550CS	19,3	675	720	605	35	16	3/4"
70WK759CC	UW-K759CC-FS	K750CC	19,3	675	720	605	35	16	3/4"
70WH709CS	UW-H709CS-FS	H700CS	19,3	675	720	605	35	16	3/4"
70WK759CS	UW-K759CS-FS	K750CS	19,0	675	720	605	35	18	3/4"
70WH759CS	UW-H759CS-FS	H750CS	19,0	675	720	605	35	18	3/4"
70WH859CB	UW-H859CB-FS	H850CB	20,1	675	720	655	35	22	1"
70WK1009CS	UW-K1009CS-FS	K1000CS	20,1	675	720	655	42	22	1"
70WK1509CS	UW-K1509CS-FS	K1500CS	20,1	675	720	655	42	22	1"
70WKP1509CS	UW-KP1509CS-FS	KP1500CS	20,1	675	720	655	42	22	1"