

APPLICAZIONE - APPLICATION - ANWENDUNG			T.N.							
Tipo	Compress.Dorin	Temp.entrata acqua	capacità frigorifera Qo - refrigerating capacity Qo - Kälteleistung Qo							
Type	Compress.Dorin	Water inlet temp.								
Typ	Verdichter Dorin	Kühlwassereintr.	temp.evapor. - evaporat.temp. - Verdampfungstemp.							
			-5°C	-10°C	-15°C	-20°C	-25°C	-30°C	-35°C	-40°C
		°C	Qo (W)							
UW-H48CC-FS	H40CC	15	1940	1600	1300	1040	820	630	480	350
UW-H78CC-FS	H75CC	15	2640	2170	1770	1430	1130	870	660	480
UW-H108CC-FS	H100CC	15	3860	3180	2590	2090	1650	1280	960	700
UW-H158CC-FS	H150CC	15	4710	3880	3160	2550	2010	1560	1170	850
UW-H188CC-FS	H180CC	15	5380	4420	3600	2890	2300	1790	1350	990
UW-H208CC-FS	H200CC	15	6030	4970	4050	3260	2580	2000	1510	1090
UW-H228CC-FS	H220CC	15	7020	5780	4710	3790	3010	2330	1750	1270
UW-H258CC-FS	H250CC	15	7780	6410	5230	4210	3330	2580	1940	1410
UW-H288CC-FS	H280CC	15	8740	7190	5850	4700	3760	2900	2180	1580
UW-H308CC-FS	H300CC	15	10380	8430	6750	5300	4210	3220	2390	1710
UF-H308CC-FS										
UW-H358CC-FS	H350CC	15	11400	9230	7370	5800	4590	3500	2600	1860
UF-H358CC-FS										
UW-H388CC-FS	H380CC	15	12530	10190	8190	6500	5200	4000	2980	2130
UF-H388CC-FS										
UW-H408CC-FS	H403CC	15	13540	11010	8860	7050	--	--	--	--
UF-H408CC-FS										
UW-H508CC-FS	H503CC	15	16670	13640	11010	8750	6810	5270	3960	2860
UF-H508CC-FS										
UW-H558CC-FS	H550CC	15	16600	13670	11070	8860	6970	5390	3990	2860
UF-H558CC-FS										
UW-H748CC-FS	H743CC	15	19710	16230	13210	10600	8430	6590	5040	3730
UF-H748CC-FS										
UW-H708CC-FS	H700CC	15	20060	16510	13390	10740	8470	6610	4950	3580
UF-H708CC-FS										
UW-K758CC-FS	K750CC	15	25030	20630	16810	13530	10730	8380	6430	4840
UF-K758CC-FS										
UW-H758CC-FS	H750CC	15	24600	20250	16400	13050	10280	7930	5920	4320
UF-H758CC-FS										
UF-K1008CC-FS	K1000CC	15	30460	24950	20200	16130	12750	9930	7590	5660
UF-K1508CC-FS	K1500CC	15	38180	31620	25950	21100	17120	13550	10630	7990
UF-K2000CC-FS	K2000CC	15	44010	36330	29710	24030	19210	15030	11500	8560
UF-KP2000CC-FS	KP2000CC	15	43730	36220	29750	24210	19520	15410	11940	9040
UF-K2508CC-FS	K2500CC	15	55630	45990	37670	30540	24470	19190	14720	10980
UF-K3008CC-FS	K3000CC	15	64730	53450	43710	35370	28100	22080	16990	12710

Funzionamento a 50 Hz - Frequency rate 50 Hz - Frequenz 50 Hz

Temperatura gas aspirato +20°C - Suction gas temperature +20°C - Sauggastemperatur +20°C

Resa frigorifera senza sottoraffreddamento del liquido - Capacity rating without liquid subcooling - Kälteleistungen ohne Flüssigkeitsunterkühlung

Temperatura condensazione +35°C - Condensing temperature +35°C - Kondens. temp. +35°C