

APPLICAZIONE - APPLICATION - ANWENDUNG			B.T.					
Tipo Type Typ	Compress.Dorin Compress.Dorin Verdichter Dorin	Temp.entrata acqua	capacità frigorifera Qo - refrigerating capacity Qo - Kälteleistung Qo					
		Water inlet temp.	potenza assorbita Pe - power input Pe - Leistungsaufnahme Pe					
		Kühlwassereintr.	temp.evapor. - evaporat.temp. - Verdampfungstemp.					
		°C	-15°C	-20°C	-25°C	-30°C	-35°C	-40°C
		Qo (W)						
UW-H59CS-FS	H50CS	15	1780	1430	1130	870	660	480
UW-H79CS-FS	H75CS	15	2600	2090	1650	1280	960	700
UW-H109CS-FS	H100CS	15	3170	2550	2010	1560	1170	850
UW-H159CS-FS	H150CS	15	3610	2910	2300	1790	1350	990
UW-H189CS-FS	H180CS	15	4060	3270	2580	2000	1510	1090
UW-H209CS-FS	H200CS	15	4730	3800	3010	2330	1750	1270
UW-H229CS-FS	H220CS	15	5250	4220	3330	2580	1940	1410
UW-H259CS-FS	H250CS	15	5960	4770	3760	2900	2180	1580
UW-H299CS-FS	H290CS	15	6760	5380	4210	3220	2390	1710
UW-H309CS-FS	H300CS	15	7360	5870	4590	3500	2600	1860
UW-H359SB-FS	H350SB	15	--	6600	5200	4000	2980	2130
UW-H389SB-FS	H380SB	15	--	7510	5960	4630	3500	2560
UW-H399CS-FS	H390CS	15	6210	7410	5860	4550	3430	2500
UF-H399CS-FS								
UW-H3929CS-FS	H392CS	15	--	9110	7220	5600	4220	3070
UF-H3929CS-FS								
UW-H409CS-FS	H403CS	15	10730	8630	6810	5270	3960	2860
UF-H409CS-FS								
UW-H459CS-FS	H450CS	15	11070	8860	6970	5390	3990	2860
UF-H459CS-FS								
UW-H509CS-FS	H503CS	15	13100	10590	8430	6590	5040	3730
UF-H509CS-FS								
UW-H559CS-FS	H550CS	15	13390	10740	8470	6610	4950	3580
UF-H559CS-FS								
UW-K759CC-FS	K750CC	15	16810	13530	10730	8380	6430	4840
UF-K759CC-FS								
UW-H709CS-FS	H700CS	15	15620	12560	9950	7780	5870	4300
UF-H709CS-FS								
UW-K759CS-FS	K750CS	15	20000	16100	12750	9930	7590	5660
UF-K759CS-FS								
UW-H759CS-FS	H750CS	15	18600	15000	11900	9370	7150	5240
UF-H759CS-FS								
UW-H850CB-FS	H850CB	15	--	17490	14020	11050	8500	6210
UF-H850CB-FS								
UW-K1009CS-FS	K1000CS	15	26200	21320	17120	13550	10530	7990
UF-K1009CS-FS								
UW-K1509CS-FS	K1500CS	15	29810	24120	19210	15030	11500	8560
UF-K1509CS-FS								
UF-K1500CB-FS	K1500CB	15	37870	30660	24470	19190	14720	10980
UF-K2500CB-FS	K2500CB	15	--	35100	28100	22080	16990	12710
UF-Y3069CB-FS	Y3060CB	15	53080	43330	34990	27890	21860	16730

Funzionamento a 50 Hz - Frequency rate 50 Hz - Frequenz 50 Hz

Temperatura gas aspirato +20°C - Suction gas temperature +20°C - Sauggastemperatur +20°C

Resa frigorifera senza sottoraffreddamento del liquido - Capacity rating without liquid subcooling - Kälteleistungen ohne Flüssigkeitsunterkühlung

Temperatura condensazione +35°C - Condensing temperature +35°C - Kondens. temp. +35°C