



Unità di compressione semiermetiche per installazioni remote
Semi-hermetic condensing units for remote installation
Halbhermetische Kondensationseinheiten fuer getrennte

Unità di compressione semiermetiche per installazioni remote

Semi-hermetic condensing units for remote installation

Halbhermetische Kondensationseinheiten fuer getrennte

Codice Frigo System	Tipo Type Typ	Compressore Compressor Verdichter DORIN	Ricevitore liquido Liquid receiver Sammler	Ingombri			Connes.-Connect.-Anschl.			
				Dimensions Abmessungen			Aspirazione Suction Austritt	Scarico Discharge Druckventil	Ritorno Return Rückfall	Liquido Liquid Flüssig
				L	P	H				
				[dm ³]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]

APPLICAZIONE - APPLICATION - ANWENDUNG				T.N.						
70RH48CC	UR-H48CC-FS	H40CC	6	505	350	460	12	12	12	10
70RH78CC	UR-H78CC-FS	H75CC	6	505	350	460	12	12	12	10
70RH108CC	UR-H108CC-FS	H100CC	6	505	350	460	16	12	12	10
70RH158CC	UR-H158CC-FS	H150CC	6	505	350	460	16	12	12	10
70RH188CC	UR-H188CC-FS	H180CC	6	505	350	460	16	12	12	10
70RH208CC	UR-H208CC-FS	H200CC	6	505	350	460	16	16	12	10
70RH228CC	UR-H228CC-FS	H220CC	6	505	350	460	18	16	12	10
70RH258CC	UR-H258CC-FS	H250CC	13	505	350	460	18	16	14	12
70RH288CC	UR-H288CC-FS	H280CC	13	550	470	540	18	16	14	12
70RH308CC	UR-H308CC-FS	H300CC	13	550	470	540	22	16	14	12
70RH358CC	UR-H358CC-FS	H350CC	19	550	470	540	28	16	18	16
70RH388CC	UR-H388CC-FS	H380CC	19	680	675	560	28	16	18	16
70RH408CC	UR-H408CC-FS	H403CC	19	680	675	560	28	16	18	16
70RH508CC	UR-H508CC-FS	H503CC	19	680	675	560	28	16	18	16
70RH558CC	UR-H558CC-FS	H550CC	19	680	675	560	28	18	18	16
70RH748CC	UR-H748CC-FS	H743CC	19	680	675	560	35	16	22	18
70RH708CC	UR-H708CC-FS	H700CC	19	680	675	560	35	18	22	18
70RK758CC	UR-K758CC-FS	K750CC	2 x 19,0	720	675	565	35	22	22	18
70RH758CC	UR-H758CC-FS	H750CC	2 x 19,0	720	675	565	35	22	22	18
70RK1008CC	UR-K1008CC-FS	K1000CC	2 x 19,0	720	675	565	35	28	22	18
70RK1508CC	UR-K1508CC-FS	K1500CC	2 x 19,0	720	675	565	42	28	28	22
70RK2008CC	UR-K2008CC-FS	K2000CC	2 x 19,0	1406	490	565	42	28	35	28
70RKP2008CC	UR-KP2008CC-FS	KP2000CC	2 x 19,0	1406	490	565	42	28	35	28
70RK2508CC	UR-K2508CC-FS	K2500CC	PER DIMENSIONI CONTATTARE IL NS. UFFICIO TECNICO				42	28	35	28
70RK3008CC	UR-K3008CC-FS	K3000CC					54	35	35	28
70RY3568CC	UR-Y3568CC-FS	Y3560CC					54	35	54	35
70RY4068CC	UR-Y4068CC-FS	Y4060CC					54	35	54	35
70RY4568CC	UR-Y4568CC-FS	Y4560CC					54	42	54	42
70RY5068CC	UR-Y5068CC-FS	Y5060CC					54	42	54	42
70RY5088CC	UR-Y5088CC-FS	Y5080CC					66	42	66	42
70RY5588CC	UR-Y5588CC-FS	Y5580CC					66	42	66	42
70RY6088CC	UR-Y6088CC-FS	Y6080CC					80	42	80	42
70RY7588CC	UR-Y7588CC-FS	Y7580CC					80	42	80	42

Unità di compressione semiermetiche per installazioni remote

Semi-hermetic condensing units for remote installation

Halbhermetische Kondensationseinheiten fuer getrennte

Codice Frigo System	Tipo Type Typ	Compressore Compressor Verdichter DORIN	Ricevitore liquido Liquid receiver Sammler	Ingombri			Connes.-Connect.-Anschl.			
				Dimensions Abmessungen			Aspirazione Suction Austritt	Scarico Discharge Druckventil	Ritorno Return Rückfall	Liquido Liquid Flüssig
				L	P	H				
				[dm ³]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]

APPLICAZIONE - APPLICATION - ANWENDUNG				B.T.						
70RH59CS	UR-H59CS-FS	H50CS	6	505	350	460	12	12	12	10
70RH79CS	UR-H79CS-FS	H75CS	6	505	350	460	16	12	12	10
70RH109CS	UR-H109CS-FS	H100CS	6	505	350	460	16	12	12	10
70RH159CS	UR-H159CS-FS	H150CS	6	505	350	460	16	12	12	10
70RH189CS	UR-H189CS-FS	H180CS	6	505	350	460	16	12	12	10
70RH209CS	UR-H209CS-FS	H200CS	6	505	350	460	18	16	12	10
70RH229CS	UR-H229CS-FS	H220CS	6	505	350	460	18	16	12	10
70RH259CS	UR-H259CS-FS	H250CS	13	550	470	540	18	16	14	12
70RH299CS	UR-H299CS-FS	H290CS	13	550	470	540	22	16	14	12
70RH309CS	UR-H309CS-FS	H300CS	13	550	470	540	28	16	14	12
70RH359SB	UR-H359SB-FS	H350SB	13	550	470	540	28	16	14	12
70RH389SB	UR-H389SB-FS	H380SB	19	550	470	540	28	16	18	16
70RH399CS	UR-H399CS-FS	H390CS	19	550	470	540	28	16	18	16
70RH3929CS	UR-H3929CS-FS	H392CS	19	550	470	540	28	16	18	16
70RH409CS	UR-H409CS-FS	H403CS	19	680	675	560	28	16	18	16
70RH459CS	UR-H459CS-FS	H450CS	19	680	675	560	28	18	18	16
70RH509CS	UR-H509CS-FS	H503CS	19	680	675	565	35	16	18	16
70RH559CS	UR-H559CS-FS	H550CS	19	680	675	565	35	18	18	16
70RK759CC	UR-K759CC-FS	K750CC	19	720	675	565	35	22	18	16
70RKH709CS	UR-H709CS-FS	H700CS	19	720	675	565	35	22	18	16
70RK759CS	UR-K759CS-FS	K750CS	19	720	675	565	35	22	22	18
70RH759CS	UR-H759CS-FS	H750CS	19	720	675	565	35	22	22	18
70RH859CB	UR-H859CB-FS	H850CB	2 x 19,0	720	675	565	35	22	35	22
70RK1009CS	UR-K1009CS-FS	K1000CS	2 x 19,0	720	675	565	42	28	42	28
70RK1509CS	UR-K1509CS-FS	K1500CS	2 x 19,0	1406	490	565	42	28	42	28
70RKP1509CS	UR-KP1509CS-FS	KP1500CS	2 x 19,0	1406	490	565	42	28	42	28
70RK1509CB	UR-K1509CB-FS	K1500CB	2 x 19,0	1406	490	565	42	28	42	28
70RK2509CB	UR-K2509CB-FS	K2500CB	PER DIMENSIONI CONTATTARE IL NS. UFFICIO TECNICO				54	35	54	35
70RY3069CB	UR-Y3069CB-FS	Y3060CB					54	35	54	35
70RY3569CB	UR-Y3569CB-FS	Y3560CB					54	35	54	35
70RY4069CB	UR-Y4069CB-FS	Y4060CB					54	35	54	35
70RY4569CB	UR-Y4569CB-FS	Y4560CB					54	35	54	35
70RY4789CB	UR-Y4789CB-FS	Y4780CB					66	42	66	42
70RY5089CB	UR-Y5089CB-FS	Y5080CB					80	42	80	42
70RY5589CB	UR-Y5589CB-FS	Y5580CB					80	42	80	42
70RY6089CB	UR-Y6089CB-FS	Y6080CB					80	42	80	42