



CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R404A MBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-20°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm ³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

V 16.3/A	474	390	315	251	197	NB6144GK	1/6	4,51	220/1/50	285	1,80	15,3
V 15.3/A	547	446	360	289	232	NB6152GK	1/5	5,02	220/1/50	326	1,98	15,3
V 14.3L/A	658	542	441	356	284	NB6165GK	1/4	6,06	220/1/50	409	2,39	13,8
V 14.3/A	794	636	500	386	296	NE6181GK	1/4	7,38	220/1/50	385	2,33	16,5
V 13.3/A	948	773	616	479	361	NE6210GK	1/3	8,79	220/1/50	477	2,62	13,8
V 12.3/A	1389	1139	918	725	560	NE9213GK	1/2	12,1	220/1/50	800	4,40	14,1
V 34.3/A	1595	1304	1040	802	592	T6217GK	3/4	14,51	220/1/50	847	4,21	22,0
V 34.3/A2V	1595	1304	1040	802	592	T6217GK	3/4	14,51	220/1/50	862	4,21	22,0
V 100.3/A	1911	1568	1256	978	733	T6220GK	1	17,40	220/1/50	925	4,35	26,5
V 100.3/A2V	1911	1568	1256	978	733	T6220GK	1	17,40	220/1/50	966	4,35	26,5
V 110.3/A	2582	2096	1672	1312	1014	NJ9226GK	1,1	21,70	220/1/50	1099	4,24	27,5
TV 110.3/A	2582	2096	1672	1312	1014	NJ9226GS	1,1	21,70	380/3/50	1099	1,77	10,0
V 110.3/A2V	2582	2096	1672	1312	1014	NJ9226GK	1,1	21,70	220/1/50	1138	4,24	27,5
TV 110.3/A2V	2582	2096	1672	1312	1014	NJ9226GS	1,1	21,70	380/3/50	1138	1,77	10,0
V 120.3/A	3181	2574	2048	1602	1236	NJ9232GK	1,2	26,14	220/1/50	1325	5,40	33,7
TV 120.3/A	3181	2574	2048	1602	1236	NJ9232GS	1,2	26,14	380/3/50	1320	2,07	13,0
V 120.3/A2V	3181	2574	2048	1602	1236	NJ9232GK	1,2	26,14	220/1/50	1395	5,40	33,7
TV 120.3/A2V	3181	2574	2048	1602	1236	NJ9232GS	1,2	26,14	380/3/50	1390	2,07	13,0
V 150.3/A	3899	3213	2601	2065	1605	NJ9238GK	1,5	32,70	220/1/50	1655	7,03	43,0
TV 150.3/A	3899	3213	2601	2065	1605	NJ9238GS	1,5	32,70	380/3/50	1504	2,95	22,0
V 150.3/A2V	3899	3213	2601	2065	1605	NJ9238GK	1,5	32,70	220/1/50	1775	7,03	43,0
TV 150.3/A2V	3899	3213	2601	2065	1605	NJ9238GS	1,5	32,70	380/3/50	1624	2,95	22,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

C 16.3/A	474	390	315	251	197	NB6144GK	1/6	4,51	220/1/50	285	1,80	15,3
C 15.3/A	547	446	360	289	232	NB6152GK	1/5	5,02	220/1/50	326	1,98	15,3
C 14.3L/A	658	542	441	356	284	NB6165GK	1/4	6,06	220/1/50	409	2,39	13,8
C 14.3/A	794	636	500	386	296	NE6181GK	1/4	7,38	220/1/50	385	2,33	16,5
C 13.3/A	948	773	616	479	361	NE6210GK	1/3	8,79	220/1/50	477	2,62	13,8
C 12.3/A	1389	1139	918	725	560	NE9213GK	1/2	12,1	220/1/50	800	4,40	14,1
C 34.3/A	1595	1304	1040	802	592	T6217GK	3/4	14,51	220/1/50	847	4,21	22,0
C 100.3/A	1911	1568	1256	978	733	T6220GK	1	17,40	220/1/50	925	4,35	26,5
C 110.3/A	2582	2096	1672	1312	1014	NJ9226GK	1,1	21,70	220/1/50	1099	4,24	27,5
C 120.3/A	3181	2574	2048	1602	1236	NJ9232GK	1,2	26,14	220/1/50	1325	5,40	33,7

APPLICAZIONE CAPILLARE A SALDARE

APPLICATION OF CAPILLARY TO BE SOLDERED

ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN

S 16.3/A	474	390	315	251	197	NB6144GK	1/6	4,51	220/1/50	285	1,80	15,3
S 15.3/A	547	446	360	289	232	NB6152GK	1/5	5,02	220/1/50	326	1,98	15,3
S 14.3L/A	658	542	441	356	284	NB6165GK	1/4	6,06	220/1/50	409	2,39	13,8
S 14.3/A	794	636	500	386	296	NE6181GK	1/4	7,38	220/1/50	385	2,33	16,5
S 13.3/A	948	773	616	479	361	NE6210GK	1/3	8,79	220/1/50	477	2,62	13,8
S 12.3/A	1389	1139	918	725	560	NE9213GK	1/2	12,1	220/1/50	800	4,40	14,1
S 34.3/A	1595	1304	1040	802	592	T6217GK	3/4	14,51	220/1/50	847	4,21	22,0
S 100.3/A	1911	1568	1256	978	733	T6220GK	1	17,40	220/1/50	925	4,35	26,5
S 110.3/A	2582	2096	1672	1312	1014	NJ9226GK	1,1	21,70	220/1/50	1099	4,24	27,5
S 120.3/A	3181	2574	2048	1602	1236	NJ9232GK	1,2	26,14	220/1/50	1325	5,40	33,7

CON COMPRESSORE **EMBRACO - ASPERA**
 WITH **EMBRACO - ASPERA COMPRESSOR**
 MIT **EMBRACO - ASPERA KOMPRESSOR**

R404A MBP



DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello	Dimensioni - Dimensions - Abmessungen	Peso	Attacchi - Connections - Anschlüsse	
Model	Larghezza x Profondità x Altezza (mm)	Weight	Aspirazione	Liquido
Modell	Width x Depth x Height (mm)	Gewichte	Suction	Liquid
	Breite x Tiefe x Höhe (mm)	(kg)	Ansaugen	Flüssigkeit
V 16.3/A	300 x 460 x 276	17,0	3/8" - 10	1/4" - 6
V 15.3/A	300 x 460 x 276	17,0	3/8" - 10	1/4" - 6
V 14.3L/A	300 x 460 x 276	20,5	3/8" - 10	1/4" - 6
V 14.3/A	300 x 480 x 276	22,5	3/8" - 10	1/4" - 6
V 13.3/A	300 x 480 x 276	23,0	3/8" - 10	1/4" - 6
V 12.3/A	390 x 510 x 295	24,0	3/8" - 10	1/4" - 6
V 34.3/A	390 x 480 x 350	32,0	1/2" - 12	3/8" - 10
V 34.3/A2V	650 x 480 x 276	35,0	1/2" - 12	3/8" - 10
V 100.3/A	390 x 510 x 350	32,0	5/8" - 16	3/8" - 10
V 100.3/A2V	350 x 480 x 330	41,0	5/8" - 16	3/8" - 10
V 110.3/A	390 x 540 x 350	32,0	5/8" - 16	3/8" - 10
TV 110.3/A	390 x 540 x 350	36,0	5/8" - 16	3/8" - 10
V 110.3/A2V	650 x 480 x 330	45,0	5/8" - 16	3/8" - 10
TV 110.3/A2V	650 x 480 x 330	45,0	5/8" - 16	3/8" - 10
V 120.3/A	450 x 540 x 375	40,0	5/8" - 16	3/8" - 10
TV 120.3/A	450 x 540 x 375	40,0	5/8" - 16	3/8" - 10
V 120.3/A2V	650 x 480 x 330	43,0	5/8" - 16	3/8" - 10
TV 120.3/A2V	650 x 480 x 330	43,0	5/8" - 16	3/8" - 10
V 150.3/A	520 x 580 x 440	47,0	5/8" - 16	3/8" - 10
TV 150.3/A	520 x 580 x 440	47,0	5/8" - 16	3/8" - 10
V 150.3/A2V	650 x 480 x 330	45,0	5/8" - 16	3/8" - 10
TV 150.3/A2V	650 x 480 x 330	45,0	5/8" - 16	3/8" - 10
C 16.3/A	300 x 420 x 276	16,3	3/8" - 10	1/4" - 6
C 15.3/A	300 x 420 x 276	16,3	3/8" - 10	1/4" - 6
C 14.3L/A	300 x 420 x 276	19,8	3/8" - 10	1/4" - 6
C 14.3/A	300 x 460 x 276	21,8	3/8" - 10	1/4" - 6
C 13.3/A	300 x 460 x 276	22,2	3/8" - 10	1/4" - 6
C 12.3/A	390 x 480 x 295	23,2	3/8" - 10	1/4" - 6
C 34.3/A	390 x 480 x 350	30,6	1/2" - 12	3/8" - 10
C 100.3/A	390 x 480 x 350	30,6	5/8" - 16	3/8" - 10
C 110.3/A	390 x 510 x 350	30,6	5/8" - 16	3/8" - 10
C 120.3/A	450 x 540 x 375	38,6	5/8" - 16	3/8" - 10
S 16.3/A	300 x 390 x 276	15,9	8	6
S 15.3/A	300 x 390 x 276	15,9	8	6
S 14.3L/A	300 x 390 x 276	19,4	8	6
S 14.3/A	300 x 390 x 276	21,4	8	6
S 13.3/A	300 x 390 x 276	21,8	8	6
S 12.3/A	390 x 480 x 295	22,8	10	6
S 34.3/A	390 x 480 x 350	30,2	10	6
S 100.3/A	390 x 480 x 350	30,1	12	8
S 110.3/A	390 x 510 x 350	30,1	12	8
S 120.3/A	450 x 540 x 375	38,1	12	8