



CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

**R404A - R507 MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-25°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm <sup>3</sup> )	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

**APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI**

**APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES**

**ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN**

V 16.3/E	471	379	301	234	134	ML40TB	1/6	4,0	220/1/50	300	1,60	8,5
V 15.3/E	526	423	336	262	153	ML45TB	1/5	4,5	220/1/50	320	1,74	9,5
V 14.3L/E	640	511	402	310	174	ML60TB	1/4	5,7	220/1/50	360	1,95	10,6
V 14.3/E	883	708	558	431	236	ML80TB	1/4	7,6	220/1/50	460	2,55	12,8
V 13.3/E	1041	834	658	510	289	ML90TB	1/3	8,85	220/1/50	553	3,10	16,0
V 12.3/E	1442	1157	913	707	397	MP12TB	1/2	12,0	220/1/50	683	2,90	17,0
V 58.3/E	1671	1354	1082	848	488	MP14TB	5/8	14,0	220/1/50	823	3,50	19,0
V 58.3/E2V	1671	1354	1082	848	488	MP14TB	5/8	14,0	220/1/50	820	3,50	19,0
V 34.3/E	1869	1496	1178	908	500	MX16TB	3/4	15,0	220/1/50	910	4,12	23,0
V 34.3/E2V	1869	1496	1178	908	500	MX16TB	3/4	15,0	220/1/50	925	4,12	23,0
V 100.3/E	2119	1677	1299	979	496	MR18TB	1	18,12	220/1/50	965	4,54	29,5
V 100.3/E2V	2119	1677	1299	979	496	MR18TB	1	18,12	220/1/50	1004	4,54	29,5
V 110.3/E	2634	2087	1621	1230	645	MR22TB	1,1	21,74	220/1/50	1108	5,10	32,0
V 110.3/E2V	2634	2087	1621	1230	645	MR22TB	1,1	21,74	220/1/50	1147	5,10	32,0
V 120.3/E	3166	2525	1975	1508	794	MS26TB	1,2	25,95	220/1/50	1359	6,10	38,0
V 120.3/E2V	3166	2525	1975	1508	794	MS26TB	1,2	25,95	220/1/50	1345	6,10	38,0

**APPLICAZIONE CAPILLARE CON RUBINETTI**

**APPLICATION OF CAPILLARY WITH SHUT OFF VALVES**

**ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN**

C 16.3/E	471	379	301	234	134	ML40TB	1/6	4,0	220/1/50	300	1,60	8,5
C 15.3/E	526	423	336	262	153	ML45TB	1/5	4,5	220/1/50	320	1,74	9,5
C 14.3L/E	640	511	402	310	174	ML60TB	1/4	5,7	220/1/50	360	1,95	10,6
C 14.3/E	883	708	558	431	236	ML80TB	1/4	7,6	220/1/50	460	2,55	12,8
C 13.3/E	1041	834	658	510	289	ML90TB	1/3	8,85	220/1/50	553	3,10	16,0
C 12.3/E	1442	1157	913	707	397	MP12TB	1/2	12,0	220/1/50	683	2,90	17,0
C 58.3/E	1671	1354	1082	848	488	MP14TB	5/8	14,0	220/1/50	823	3,50	19,0
C 34.3/E	1869	1496	1178	908	500	MX16TB	3/4	15,0	220/1/50	910	4,12	23,0
C 100.3/E	2119	1677	1299	979	496	MR18TB	1	18,12	220/1/50	965	4,54	29,5
C 110.3/E	2634	2087	1621	1230	645	MR22TB	1,1	21,74	220/1/50	1108	5,10	32,0
C 120.3/E	3166	2525	1975	1508	794	MS26TB	1,2	25,95	220/1/50	1359	6,10	38,0

**APPLICAZIONE CAPILLARE A SALDARE**

**APPLICATION OF CAPILLARY TO BE SOLDERED**

**ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN**

S 16.3/E	471	379	301	234	134	ML40TB	1/6	4,0	220/1/50	300	1,60	8,5
S 15.3/E	526	423	336	262	153	ML45TB	1/5	4,5	220/1/50	320	1,74	9,5
S 14.3L/E	640	511	402	310	174	ML60TB	1/4	5,7	220/1/50	360	1,95	10,6
S 14.3/E	883	708	558	431	236	ML80TB	1/4	7,6	220/1/50	460	2,55	12,8
S 13.3/E	1041	834	658	510	289	ML90TB	1/3	8,85	220/1/50	553	3,10	16,0
S 12.3/E	1442	1157	913	707	397	MP12TB	1/2	12,0	220/1/50	683	2,90	17,0
S 58.3/E	1671	1354	1082	848	488	MP14TB	5/8	14,0	220/1/50	823	3,50	19,0
S 34.3/E	1869	1496	1178	908	500	MX16TB	3/4	15,0	220/1/50	910	4,12	23,0
S 100.3/E	2119	1677	1299	979	496	MR18TB	1	18,12	220/1/50	965	4,54	29,5
S 110.3/E	2634	2087	1621	1230	645	MR22TB	1,1	21,74	220/1/50	1108	5,10	32,0
S 120.3/E	3166	2525	1975	1508	794	MS26TB	1,2	25,95	220/1/50	1359	6,10	38,0

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

**R404A - R507 MBP/MHBP**



Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse	
			Aspirazione	Liquido
			Suction	Liquid
			Ansaugen	Flüssigkeit
V 16.3/E	300 x 460 x 276	17,0	3/8" - 10	1/4" - 6
V 15.3/E	300 x 460 x 276	17,0	3/8" - 10	1/4" - 6
V 14.3L/E	300 x 460 x 276	20,5	3/8" - 10	1/4" - 6
V 14.3/E	300 x 480 x 276	22,5	3/8" - 10	1/4" - 6
V 13.3/E	300 x 480 x 276	23,0	3/8" - 10	1/4" - 6
V 12.3/E	390 x 510 x 295	24,0	3/8" - 10	1/4" - 6
V 58.3/E	390 x 510 x 295	31,0	3/8" - 10	1/4" - 6
V 58.3/E2V	650 x 480 x 276	33,0	3/8" - 10	1/4" - 6
V 34.3/E	390 x 480 x 350	32,0	1/2" - 12	3/8" - 10
V 34.3/E2V	650 x 480 x 276	35,0	1/2" - 12	3/8" - 10
V 100.3/E	390 x 510 x 350	32,0	5/8" - 16	3/8" - 10
V 100.3/E2V	650 x 480 x 330	41,0	5/8" - 16	3/8" - 10
V 110.3/E	390 x 540 x 350	32,0	5/8" - 16	3/8" - 10
V 110.3/E2V	650 x 480 x 330	45,0	5/8" - 16	3/8" - 10
V 120.3/E	450 x 540 x 375	39,7	5/8" - 16	3/8" - 10
V 120.3/E2V	650 x 480 x 330	43,0	5/8" - 16	3/8" - 10
C 16.3/E	300 x 420 x 276	16,3	3/8" - 10	1/4" - 6
C 15.3/E	300 x 420 x 276	16,3	3/8" - 10	1/4" - 6
C 14.3L/E	300 x 480 x 276	19,8	3/8" - 10	1/4" - 6
C 14.3/E	300 x 460 x 276	21,8	3/8" - 10	1/4" - 6
C 13.3/E	300 x 460 x 276	22,2	3/8" - 10	1/4" - 6
C 12.3/E	390 x 480 x 295	23,2	3/8" - 10	1/4" - 6
C 58.3/E	390 x 480 x 295	30,2	3/8" - 10	1/4" - 6
C 34.3/E	390 x 480 x 350	30,6	1/2" - 12	3/8" - 10
C 100.3/E	390 x 480 x 350	30,6	5/8" - 16	3/8" - 10
C 110.3/E	390 x 510 x 350	30,6	5/8" - 16	3/8" - 10
C 120.3/E	450 x 540 x 375	38,3	5/8" - 16	3/8" - 10
S 16.3/E	300 x 390 x 276	15,9	8	6
S 15.3/E	300 x 390 x 276	15,9	8	6
S 14.3L/E	300 x 390 x 276	19,4	8	6
S 14.3/E	300 x 390 x 276	21,4	8	6
S 13.3/E	300 x 390 x 276	21,8	8	6
S 12.3/E	390 x 480 x 295	22,8	8	6
S 58.3/E	390 x 480 x 295	29,8	8	6
S 34.3/E	390 x 480 x 350	30,1	12	8
S 100.3/E	390 x 480 x 350	30,1	12	8
S 110.3/E	390 x 510 x 350	30,1	12	8
S 120.3/E	450 x 540 x 375	37,8	12	8