



CON COMPRESSORE L' UNITE' HERMETIQUE  
**WITH L' UNITE' HERMETIQUE COMPRESSOR**  
**MIT L' UNITE' HERMETIQUE KOMPRESSOR**

**R 22 MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-20°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

**APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI**  
**APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES**  
**ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN**

V 15.5	475	381	<b>300</b>	230		AEZ4425E	1/5	4,50	220/1/50	320	1,70	9
V 14.5L	618	498	<b>394</b>	306		AEZ4430E	1/4	5,70	220/1/50	387	2,13	11
V 14.5	842	680	<b>544</b>	433		AEZ4440E	1/4	7,55	220/1/50	471	2,45	18
V 13.5	1028	822	<b>649</b>	510		CAE4450E	1/3	9,40	220/1/50	576	3,11	15
V 12.5	1300	1049	<b>837</b>	663	417	CAE9460T	1/2	11,30	220/1/50	684	3,02	15,2
V 58.5	1817	1475	<b>1183</b>	941	748	CAJ9480T	5/8	15,20	220/1/50	838	3,51	22
TV 58.5	1817	1475	<b>1183</b>	941	748	TAJ9480T	5/8	15,20	380/3/50	873	1,59	13
V 58.5/2V	1817	1475	<b>1183</b>	941	748	CAJ9480T	5/8	15,20	220/1/50	848	3,51	22
TV 58.5/2V	1817	1475	<b>1183</b>	941	748	TAJ9480T	5/8	15,20	380/3/50	883	1,59	13
V 100.5L	2189	1786	<b>1438</b>	1144	903	CAJ9510T	1	18,30	220/1/50	1074	4,53	29
V 100.5L/2V	2189	1786	<b>1438</b>	1144	903	CAJ9510T	1	18,30	220/1/50	1115	4,53	29
TV 100.5L	2189	1786	<b>1438</b>	1144	903	TAJ9510T	1	18,30	380/3/50	1074	1,76	13
TV 100.5L/2V	2189	1786	<b>1438</b>	1144	903	TAJ9510T	1	18,30	380/3/50	1137	1,76	13
V 110.5	2765	2190	<b>1697</b>	1284	949	CAJ9513T	1,1	24,20	220/1/50	1287	5,64	30
V 110.5/2V	2765	2190	<b>1697</b>	1284	949	CAJ9513T	1,1	24,20	220/1/50	1328	5,64	30
TV 110.5	2765	2190	<b>1697</b>	1284	949	TAJ9513T	1,1	24,20	380/3/50	1275	2,14	13
TV 110.5/2V	2765	2190	<b>1697</b>	1284	949	TAJ9513T	1,1	24,20	380/3/50	1316	2,14	13
V 120.5	3131	2511	<b>1960</b>	1478		CAJ4517E	1,2	25,95	220/1/50	1451	5,86	35
V 120.5/2V	3131	2511	<b>1960</b>	1478		CAJ4517E	1,2	25,95	220/1/50	1437	5,86	35
TV 120.5	3131	2511	<b>1960</b>	1478		TAJ4517T	1,2	25,95	380/3/50	1496	2,31	18
TV 120.5/2V	3131	2511	<b>1960</b>	1478		TAJ4517T	1,2	25,95	380/3/50	1482	2,31	18
TV 150.5	4134	3368	<b>2701</b>	2131		TAJ4519T	1,5	34,45	380/3/50	1840	3,04	44
TV 150.5/2V	4134	3368	<b>2701</b>	2131		TAJ4519T	1,5	34,45	380/3/50	1876	3,04	44
V 200.5	4743	3725	<b>2880</b>	2205		FH4524F	2	43,50	220/1/50	2168	9,12	51
V 200.5/2V	4743	3725	<b>2880</b>	2205		FH4524F	2	43,50	220/1/50	2288	9,12	51
TV 200.5	4743	3725	<b>2880</b>	2205		TFH4524T	2	43,50	380/3/50	2177	3,66	24
TV 200.5/2V	4743	3725	<b>2880</b>	2205		TFH4524T	2	43,50	380/3/50	2297	3,66	24
V 250.5	6498	5225	<b>4107</b>	3139		FH4531F	2,5	56,65	220/1/50	2873	12,80	66
V 250.5/2V	6498	5225	<b>4107</b>	3139		FH4531F	2,5	56,65	220/1/50	3068	12,80	66
TV 250.5	6498	5225	<b>4107</b>	3139		TFH4531F	2,5	56,65	380/3/50	2248	3,75	27
TV 250.5/2V	6498	5225	<b>4107</b>	3139		TFH4531F	2,5	56,65	380/3/50	2443	3,75	27
TV 300.5	8418	6643	<b>5038</b>	3597		TFH4540F	3	74,25	380/3/50	2723	4,68	36
TV 300.5/2V	8418	6643	<b>5038</b>	3597		TFH4540F	3	74,25	380/3/50	2818	4,68	36
TV 400.5/2V	9088	7000	<b>5267</b>	3851		TAG4546T	4	90,20	380/3/50	2791	4,78	40
TV 450.5/2V	10554	8226	<b>6254</b>	4602		TAG4553T	4,5	100,70	380/3/50	3236	5,44	45
TV 500.5/2V	12172	9470	<b>7213</b>	5355		TAG4561T	5	112,50	380/3/50	3730	6,80	51
TV 600.5/2V	13727	10657	<b>8100</b>	6046		TAG4568T	6	124,40	380/3/50	4083	6,79	54
TV 614.5/2V	14713	11529	<b>8891</b>	6735		TAG4573T	6,2	134,80	380/3/50	4410	7,98	56
TV 800.5/2V	17934	13618	<b>10204</b>	10204		TAN5590H	8	182,00	380/3/50	5581	9,56	80
TV 900.5/2V	20886	16144	<b>12531</b>			TAN5610H	9	195,00	380/3/50	6551	10,90	90
TV 1000.5/2V	24266	18782	<b>14347</b>			TAN5612H	10	229,00	380/3/50	7520	13,60	102
TV 1200.5/2V	27201	21141	<b>16376</b>			TAN5614H	12	260,00	380/3/50	8226	13,60	108

**APPLICAZIONE CAPILLARE CON RUBINETTI**  
**APPLICATION OF CAPILLARY WITH SHUT OFF VALVES**  
**ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN**

C 15.5	475	381	<b>300</b>	230		AEZ4425E	1/5	4,50	220/1/50	320	1,70	9
C 14.5L	618	498	<b>394</b>	306		AEZ4430E	1/4	5,70	220/1/50	387	2,13	11
C 14.5	842	680	<b>544</b>	433		AEZ4440E	1/4	7,55	220/1/50	471	2,45	18
C 13.5	1028	822	<b>649</b>	510		CAE4450E	1/3	9,40	220/1/50	576	3,11	15
C 12.5	1300	1049	<b>837</b>	663	417	CAE9460T	1/2	11,30	220/1/50	684	3,02	15,2
C 58.5	1817	1475	<b>1183</b>	941	748	CAJ9480T	5/8	15,20	220/1/50	838	3,51	22
C 100.5L	2189	1786	<b>1438</b>	1144	903	CAJ9510T	1	18,30	220/1/50	1074	4,53	29
C 110.5	2765	2190	<b>1697</b>	1284	949	CAJ9513T	1,1	24,20	220/1/50	1287	5,64	30
C 120.5	3131	2511	<b>1960</b>	1478		CAJ4517E	1,2	25,95	220/1/50	1451	5,86	35

**APPLICAZIONE CAPILLARE A SILDARE**  
**APPLICATION OF CAPILLARY TO BE SOLDERED**  
**ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN**

S 15.5	475	381	<b>300</b>	230		AEZ4425E	1/5	4,50	220/1/50	320	1,70	9
S 14.5L	618	498	<b>394</b>	306		AEZ4430E	1/4	5,70	220/1/50	387	2,13	11
S 14.5	842	680	<b>544</b>	433		AEZ4440E	1/4	7,55	220/1/50	471	2,45	18
S 13.5	1028	822	<b>649</b>	510		CAE4450E	1/3	9,40	220/1/50	576	3,11	15
S 12.5	1300	1049	<b>837</b>	663	417	CAE9460T	1/2	11,30	220/1/50	684	3,02	15,2
S 58.5	1817	1475	<b>1183</b>	941	748	CAJ9480T	5/8	15,20	220/1/50	838	3,51	22
S 100.5L	2189	1786	<b>1438</b>	1144	903	CAJ9510T	1	18,30	220/1/50	1074	4,53	29
S 110.5	2765	2190	<b>1697</b>	1284	949	CAJ9513T	1,1	24,20	220/1/50	1287	5,64	30
S 120.5	3131	2511	<b>1960</b>	1478		CAJ4517E	1,2	25,95	220/1/50	1451	5,86	35

CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R 22 MBP/MHBP**



DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen			Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse	
	Larghezza x Profondità x Altezza (mm)				Aspirazione Suction Ansaugen	Liquido Liquid Flüssigkeit
	Width x Depth x Height (mm)					
	Breite x Tiefe x Höhe (mm)					
V 15.5	300 x 460 x 276			17,0	3/8" - 10	1/4" - 6
V 14.5L	300 x 460 x 276			20,5	3/8" - 10	1/4" - 6
V 14.5	300 x 480 x 276			22,5	3/8" - 10	1/4" - 6
V 13.5	300 x 480 x 276			23,0	3/8" - 10	1/4" - 6
V 12.5	300 x 540 x 276			24,0	1/2" - 12	1/4" - 6
V 58.5	390 x 480 x 350			34,6	1/2" - 12	3/8" - 10
TV 58.5	390 x 480 x 350			30,5	1/2" - 12	3/8" - 10
V 58.5/2V	650 x 480 x 330			33,0	1/2" - 12	3/8" - 10
TV 58.5/2V	650 x 480 x 330			33,0	1/2" - 12	3/8" - 10
V 100.5L	390 x 510 x 350			35,5	5/8" - 16	3/8" - 10
V 100.5L/2V	650 x 480 x 330			41,0	5/8" - 16	3/8" - 10
TV 100.5L	390 x 510 x 350			34,9	5/8" - 16	3/8" - 10
TV 100.5L/2V	650 x 480 x 330			43,0	5/8" - 16	3/8" - 10
V 110.5	390 x 540 x 350			39,7	5/8" - 16	3/8" - 10
V 110.5/2V	650 x 480 x 330			46,0	5/8" - 16	3/8" - 10
TV 110.5	390 x 540 x 350			36,0	5/8" - 16	3/8" - 10
TV 110.5/2V	650 x 480 x 330			43,0	5/8" - 16	3/8" - 10
V 120.5	450 x 540 x 375			39,7	5/8" - 16	3/8" - 10
V 120.5/2V	650 x 480 x 330			46,0	5/8" - 16	3/8" - 10
TV 120.5	450 x 540 x 375			36,0	5/8" - 16	3/8" - 10
TV 120.5/2V	650 x 480 x 330			43,0	5/8" - 16	3/8" - 10
TV 150.5	520 x 580 x 440			47,0	5/8" - 16	3/8" - 10
TV 150.5/2V	650 x 480 x 330			45,0	5/8" - 16	3/8" - 10
V 200.5	520 x 580 x 440			48,0	5/8" - 16	3/8" - 10
V 200.5/2V	790 x 580 x 420			51,0	5/8" - 16	3/8" - 10
TV 200.5	520 x 580 x 440			48,0	5/8" - 16	3/8" - 10
TV 200.5/2V	790 x 580 x 420			51,0	5/8" - 16	3/8" - 10
V 250.5	760 x 650 x 560			59,0	7/8" - 22	3/8" - 10
V 250.5/2V	790 x 580 x 420			56,0	7/8" - 22	3/8" - 10
TV 250.5	760 x 650 x 560			59,0	7/8" - 22	3/8" - 10
TV 250.5/2V	790 x 580 x 420			56,0	7/8" - 22	3/8" - 10
TV 300.5	760 x 650 x 560			74,0	7/8" - 22	1/2" - 12
TV 300.5/2V	900 x 650 x 465			83,0	7/8" - 22	1/2" - 12
TV 400.5/2V	940 x 650 x 560			80,0	7/8" - 22	1/2" - 12
TV 450.5/2V	940 x 650 x 560			92,0	7/8" - 22	5/8" - 16
TV 500.5/2V	1190 x 850 x 640			94,0	1.1/8" - 28	5/8" - 16
TV 600.5/2V	1190 x 850 x 640			100,0	1.1/8" - 28	5/8" - 16
TV 614.5/2V	1190 x 850 x 640			100,0	1.1/8" - 28	5/8" - 16
TV 800.5/2V	1290 x 1000 x 875			200,0	1.1/8" - 28	3/4" - 18
TV 900.5/2V	1290 x 1000 x 875			210,0	1.1/8" - 28	3/4" - 18
TV 1000.5/2V	1290 x 1000 x 875			200,0	1.3/8" - 35	3/4" - 18
TV 1200.5/2V	1290 x 1000 x 875			250,0	1.3/8" - 35	3/4" - 18
C 15.5	300 x 420 x 276			16,3	3/8" - 10	1/4" - 6
C 14.5L	300 x 420 x 276			19,8	3/8" - 10	1/4" - 6
C 14.5	300 x 460 x 276			21,8	3/8" - 10	1/4" - 6
C 13.5	300 x 480 x 276			22,3	3/8" - 10	1/4" - 6
C 12.5	300 x 510 x 276			23,2	1/2" - 12	1/4" - 6
C 58.5	390 x 480 x 350			33,2	1/2" - 12	3/8" - 10
C 100.5L	390 x 480 x 350			34,1	5/8" - 16	3/8" - 10
C 110.5	390 x 510 x 350			38,3	5/8" - 16	3/8" - 10
C 120.5	450 x 540 x 375			38,3	5/8" - 16	3/8" - 10
S 15.5	300 x 390 x 276			15,9	8	6
S 14.5L	300 x 390 x 276			19,4	8	6
S 14.5	300 x 390 x 276			21,4	8	6
S 13.5	300 x 390 x 276			21,9	8	6
S 12.5	300 x 510 x 276			22,8	10	6
S 58.5	390 x 480 x 350			32,7	12	8
S 100.5L	390 x 480 x 350			33,6	16	8
S 110.5	390 x 510 x 350			37,8	16	8
S 120.5	450 x 540 x 375			37,8	16	8