



CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

**R 22 MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-25°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm <sup>3</sup> )	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

V 16.5/E	469	380	302	236	131	L40TN	1/6	4,04	220/1/50	257	1,37	8,7
V 15.5/E	510	413	328	255	142	L45TN	1/5	4,50	220/1/50	271	1,44	9,0
V 14.5L/E	641	519	413	320	176	L57TN	1/4	5,67	220/1/50	302	1,60	9,0
V 14.5/E	861	702	563	444	258	L76TN	1/4	7,57	220/1/50	405	2,23	12,3
V 13.5/E	1016	823	654	508	282	L88TN	1/3	8,85	220/1/50	478	2,67	15,8
V 12.5/E	1379	1110	877	678	375	P12TN	1/2	12,00	220/1/50	569	2,34	14,0
V 58.5/E	1803	1437	1121	853	450	S15TN-T	5/8	15,20	220/1/50	670	3,40	22,0
V 34.5/E	2132	1705	1337	1026	562	R18TN-T	3/4	18,12	220/1/50	825	3,50	24,2
V 34.5/E2V	2132	1705	1337	1026	562	R18TN-T	3/4	18,12	220/1/50	866	3,50	24,2
V 100.5L/E	2607	2062	1594	1197	604	S22TN-T	1	21,78	220/1/50	915	4,10	32,0
V 100.5L/E2V	2607	2062	1594	1197	604	S22TN-T	1	21,78	220/1/50	956	4,10	32,0
V 120.5/E	3195	2567	2013	1530	760	S26TN-T	1,2	25,95	220/1/50	1220	5,40	35,0
V 120.5/E2V	3195	2567	2013	1530	760	S26TN-T	1,2	25,95	220/1/50	1206	5,40	35,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

C 16.5/E	469	380	302	236	131	L40TN	1/6	4,04	220/1/50	257	1,37	8,7
C 15.5/E	510	413	328	255	142	L45TN	1/5	4,50	220/1/50	271	1,44	9,0
C 14.5L/E	641	519	413	320	176	L57TN	1/4	5,67	220/1/50	302	1,60	9,0
C 14.5/E	861	702	563	444	258	L76TN	1/4	7,57	220/1/50	405	2,23	12,3
C 13.5/E	1016	823	654	508	282	L88TN	1/3	8,85	220/1/50	478	2,67	15,8
C 12.5/E	1379	1110	877	678	375	P12TN	1/2	12,00	220/1/50	569	2,34	14,0
C 58.5/E	1803	1437	1121	853	450	S15TN-T	5/8	15,20	220/1/50	670	3,40	22,0
C 34.5/E	2132	1705	1337	1026	562	R18TN-T	3/4	18,12	220/1/50	825	3,50	24,2
C 100.5L/E	2607	2062	1594	1197	604	S22TN-T	1	21,78	220/1/50	915	4,10	32,0
C 120.5/E	3195	2567	2013	1530	760	S26TN-T	1,2	25,95	220/1/50	1220	5,40	35,0

APPLICAZIONE CAPILLARE A SILDARE

APPLICATION OF CAPILLARY TO BE SOLDERED

ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN

S 16.5/E						L40TN	1/6	4,04	220/1/50	257	1,37	8,7
S 15.5/E						L45TN	1/5	4,50	220/1/50	271	1,44	9,0
S 14.5L/E						L57TN	1/4	5,67	220/1/50	302	1,60	9,0
S 14.5/E						L76TN	1/4	7,57	220/1/50	405	2,23	12,3
S 13.5/E						L88TN	1/3	8,85	220/1/50	478	2,67	15,8
S 12.5/E						P12TN	1/2	12,00	220/1/50	569	2,34	14,0
S 58.5/E						S15TN-T	5/8	15,20	220/1/50	670	3,40	22,0
S 34.5/E						R18TN-T	3/4	18,12	220/1/50	825	3,50	24,2
S 100.5L/E						S22TN-T	1	21,78	220/1/50	915	4,10	32,0
S 120.5/E						S26TN-T	1,2	25,95	220/1/50	1220	5,40	35,0

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

**R 22 MBP/MHBP**



Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse	
			Aspirazione	Liquido
			Suction	Liquid
			Ansaugen	Flüssigkeit
V 16.5/E	300 x 460 x 276	16,0	3/8" - 10	1/4" - 6
V 15.5/E	300 x 460 x 276	17,0	3/8" - 10	1/4" - 6
V 14.5L/E	300 x 460 x 276	20,5	3/8" - 10	1/4" - 6
V 14.5/E	300 x 480 x 276	24,0	3/8" - 10	1/4" - 6
V 13.5/E	300 x 480 x 276	22,0	3/8" - 10	1/4" - 6
V 12.5/E	300 x 540 x 276	30,0	1/2" - 12	1/4" - 6
V 58.5/E	390 x 480 x 350	31,0	1/2" - 12	3/8" - 10
V 34.5/E	390 x 510 x 350	32,0	1/2" - 12	3/8" - 10
V 34.5/E2V	650 x 480 x 330	35,0	1/2" - 12	3/8" - 10
V 100.5L/E	390 x 540 x 350	35,5	1/2" - 12	3/8" - 10
V 100.5L/E2V	650 x 480 x 330	41,0	1/2" - 12	3/8" - 10
V 120.5/E	450 x 540 x 375	36,0	1/2" - 12	3/8" - 10
V 120.5/E2V	650 x 480 x 330	43,0	1/2" - 12	3/8" - 10
C 16.5/E	300 x 420 x 276	15,3	3/8" - 10	1/4" - 6
C 15.5/E	300 x 420 x 276	16,3	3/8" - 10	1/4" - 6
C 14.5L/E	300 x 420 x 276	19,8	3/8" - 10	1/4" - 6
C 14.5/E	300 x 460 x 276	23,3	3/8" - 10	1/4" - 6
C 13.5/E	300 x 460 x 276	21,3	3/8" - 10	1/4" - 6
C 12.5/E	300 x 510 x 276	29,2	1/2" - 12	1/4" - 6
C 58.5/E	390 x 480 x 350	30,2	1/2" - 12	3/8" - 10
C 34.5/E	390 x 480 x 350	30,6	1/2" - 12	3/8" - 10
C 100.5L/E	390 x 510 x 350	34,1	1/2" - 12	3/8" - 10
C 120.5/E	450 x 540 x 375	34,6	1/2" - 12	3/8" - 10
S 16.5/E	300 x 390 x 276	14,9	8	6
S 15.5/E	300 x 390 x 276	15,9	8	6
S 14.5L/E	300 x 390 x 276	19,4	8	6
S 14.5/E	300 x 390 x 276	22,9	8	6
S 13.5/E	300 x 390 x 276	20,9	8	6
S 12.5/E	300 x 510 x 276	28,8	10	6
S 58.5/E	390 x 480 x 350	29,8	10	8
S 34.5/E	390 x 480 x 350	30,1	10	8
S 100.5L/E	390 x 510 x 350	33,6	12	8
S 120.5/E	450 x 540 x 375	34,1	12	8