



CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R134a MBP/MHBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)				Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm ³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

V 15.11/A	401	325	261	207	NB6144Z	1/5	6,06	220/1/50	233	1,26	7,5
V 14.11L/A	501	389	297	226	NE6160Z	1/4	8,00	220/1/50	232	1,49	10,8
V 14.11/A	588	463	358	273	NE6170Z	1/4	8,79	220/1/50	265	1,57	11,0
V 13.11/A	818	651	510	395	NE6187Z	1/3	12,10	220/1/50	380	2,41	13,8
V 12.11/A	1089	852	640	455	T6213Z	1/2	17,40	220/1/50	581	3,48	20,0
V 58.11/A	1305	1017	780	595	T6215Z	5/8	20,40	220/1/50	597	3,71	21,0
V 34.11/A	1816	1425	1099	837	NJ6220Z	3/4	25,80	220/1/50	792	4,65	35,0
V 34.11/A2V	1816	1425	1099	837	NJ6220Z	3/4	25,80	220/1/50	747	4,65	35,0
TV 34.11/A	1816	1425	1099	837	NJ6220ZX	3/4	25,80	380/3/50	706	1,23	10,0
TV 34.11/A2V	1816	1425	1099	837	NJ6220ZX	3/4	25,80	380/3/50	661	1,23	10,0
V 100.11/A	2379	1939	1558	1236	NJ6226Z	1	34,37	220/1/50	925	5,75	31,0
V 100.11/A2V	2379	1939	1558	1236	NJ6226Z	1	34,37	220/1/50	966	5,75	31,0
TV 100.11/A	2379	1939	1558	1236	NJ6226ZX	1	34,37	380/3/50	922	1,80	13,0
TV 100.11/A2V	2379	1939	1558	1236	NJ6226ZX	1	34,37	380/3/50	963	1,80	13,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

C 18.11/A	263	210	165	130	NB5128Z	1/8	4,51	220/1/50	153	0,90	11,2
C 16.11/A	288	230	181	141	NB5132Z	1/6	5,02	220/1/50	185	0,90	8,3
C 15.11/A	401	325	261	207	NB6144Z	1/5	6,06	220/1/50	233	1,26	7,5
C 14.11L/A	501	389	297	226	NE6160Z	1/4	8,00	220/1/50	232	1,49	10,8
C 14.11/A	588	463	358	273	NE6170Z	1/4	8,79	220/1/50	265	1,57	11,0
C 13.11/A	818	651	510	395	NE6187Z	1/3	12,10	220/1/50	380	2,41	13,8
C 12.11/A	1089	852	640	455	T6213Z	1/2	17,40	220/1/50	581	3,48	20,0
C 58.11/A	1305	1017	780	595	T6215Z	5/8	20,40	220/1/50	597	3,71	21,0
C 34.11/A	1816	1425	1099	837	NJ6220Z	3/4	25,80	220/1/50	792	4,65	35,0
C 100.11/A	2379	1939	1558	1236	NJ6226Z	1	34,37	220/1/50	925	5,75	31,0

APPLICAZIONE CAPILLARE A SILDARE

APPLICATION OF CAPILLARY TO BE SOLDERED

ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN

S 18.11/A	263	210	165	130	NB5128Z	1/8	4,51	220/1/50	153	0,90	11,2
S 16.11/A	288	230	181	141	NB5132Z	1/6	5,02	220/1/50	185	0,90	8,3
S 15.11/A	401	325	261	207	NB6144Z	1/5	6,06	220/1/50	233	1,26	7,5
S 14.11L/A	501	389	297	226	NE6160Z	1/4	8,00	220/1/50	232	1,49	10,8
S 14.11/A	588	463	358	273	NE6170Z	1/4	8,79	220/1/50	265	1,57	11,0
S 13.11/A	818	651	510	395	NE6187Z	1/3	12,10	220/1/50	380	2,41	13,8
S 12.11/A	1089	852	640	455	T6213Z	1/2	17,40	220/1/50	581	3,48	20,0
S 58.11/A	1305	1017	780	595	T6215Z	5/8	20,40	220/1/50	597	3,71	21,0
S 34.11/A	1816	1425	1099	837	NJ6220Z	3/4	25,80	220/1/50	792	4,65	35,0
S 100.11/A	2379	1939	1558	1236	NJ6226Z	1	34,37	220/1/50	925	5,75	31,0

CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R134a MBP/MHBP



DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen			Attacchi - Connections - Anschlüsse		
	Larghezza x Profondità x Altezza (mm)			Aspirazione Suction Ansaugen	Liquido Liquid Flüssigkeit	
	Width x Depth x Height (mm)					
	Breite x Tiefe x Höhe (mm)			Weight Gewichte (kg)		
V 15.11/A	300	x 460	x 276	17,0	3/8" - 10	1/4" - 6
V 14.11L/A	300	x 460	x 276	18,0	3/8" - 10	1/4" - 6
V 14.11/A	300	x 460	x 276	18,3	3/8" - 10	1/4" - 6
V 13.11/A	300	x 480	x 276	20,5	3/8" - 10	1/4" - 6
V 12.11/A	300	x 540	x 276	24,0	1/2" - 10	1/4" - 6
V 58.11/A	390	x 510	x 350	26,5	1/2" - 10	3/8" - 10
V 34.11/A	390	x 510	x 350	35,0	1/2" - 10	3/8" - 10
V 34.11/A2V	650	x 480	x 330	40,0	1/2" - 10	3/8" - 10
TV 34.11/A	390	x 510	x 350	33,9	1/2" - 10	3/8" - 10
TV 34.11/A2V	650	x 480	x 330	39,5	1/2" - 10	3/8" - 10
V 100.11/A	390	x 540	x 350	39,0	1/2" - 10	3/8" - 10
V 100.11/A2V	650	x 480	x 330	46,0	1/2" - 10	3/8" - 10
TV 100.11/A	390	x 540	x 350	35,0	1/2" - 10	3/8" - 10
TV 100.11/A2V	650	x 480	x 330	43,0	1/2" - 10	3/8" - 10
C 18.11/A	300	x 420	x 276	13,5	3/8" - 10	1/4" - 6
C 16.11/A	300	x 420	x 276	14,0	3/8" - 10	1/4" - 6
C 15.11/A	300	x 420	x 276	16,3	3/8" - 10	1/4" - 6
C 14.11L/A	300	x 420	x 276	17,3	3/8" - 10	1/4" - 6
C 14.11/A	300	x 460	x 276	17,6	3/8" - 10	1/4" - 6
C 13.11/A	300	x 460	x 276	19,7	3/8" - 10	1/4" - 6
C 12.11/A	300	x 510	x 276	23,2	1/2" - 10	1/4" - 6
C 58.11/A	390	x 510	x 350	25,1	1/2" - 10	3/8" - 10
C 34.11/A	390	x 480	x 350	33,6	1/2" - 10	3/8" - 10
C 100.11/A	390	x 510	x 350	37,6	1/2" - 10	3/8" - 10
S 18.11/A	300	x 390	x 276	13,1	8	6
S 16.11/A	300	x 390	x 276	13,6	8	6
S 15.11/A	300	x 390	x 276	15,9	8	6
S 14.11L/A	300	x 390	x 276	16,9	8	6
S 14.11/A	300	x 390	x 276	17,2	8	6
S 13.11/A	300	x 390	x 276	19,3	8	6
S 12.11/A	300	x 510	x 276	22,8	10	6
S 58.11/A	390	x 510	x 350	24,7	10	6
S 34.11/A	390	x 480	x 350	33,1	12	8
S 100.11/A	390	x 510	x 350	37,1	12	8