



CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

**R134a MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung				Caratteristiche compressore			Caratteristiche elettriche			
	(Watt)				Compressor characteristics			Electrical data			
					Kompressormerkmale			Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm <sup>3</sup> )	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

V 15.11/E	403	318	246	186	99	GL60TB	1/5	5,70	220/1/50	218	1,23	8,2
V 14.11L/E	517	408	315	237	122	GL80TB	1/4	7,60	220/1/50	265	1,50	9,7
V 14.11/E	615	485	375	282	146	GL90TB	1/4	8,80	220/1/50	293	1,66	12,0
V 13.11/E	862	680	524	392	193	GP12TB	1/3	12,00	220/1/50	390	2,30	13,5
V 38.11/E	937	736	565	422	211	GP14TB	3/8	14,00	220/1/50	440	2,60	18,0
V 12.11/E	1327	1053	807	589	226	GR18TB-T	1/2	18,12	220/1/50	540	3,50	22,0
V 58.11/E	1709	1349	1030	748	289	GR22TB-T	5/8	21,78	220/1/50	670	4,21	26,0
V 34.11/E	1948	1518	1146	829	346	GS26TB-T	3/4	25,95	220/1/50	825	5,00	32,0
V 34.11/E2V	1948	1518	1146	829	346	GS26TB-T	3/4	25,95	220/1/50	780	5,00	32,0
V 34.11P/E	2211	1695	1260	901	391	GS30TB-T	3/4	29,93	220/1/50	855	3,90	29,0
V 34.11P/E2V	2211	1695	1260	901	391	GS30TB-T	3/4	29,93	220/1/50	810	3,90	29,0
V 100.11/E	2320	1913	1536	1212	525	GS34TB-T	1	34,25	220/1/50	1025	4,90	32,0
V 100.11/E2V	2320	1913	1536	1212	525	GS34TB-T	1	34,25	220/1/50	1066	4,90	32,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

C 16.11/E	324	255	198	149	79	GL45TB	1/6	4,50	220/1/50	185	1,04	8,0
C 15.11/E	403	318	246	186	99	GL60TB	1/5	5,70	220/1/50	218	1,23	8,2
C 14.11L/E	517	408	315	237	122	GL80TB	1/4	7,60	220/1/50	265	1,50	9,7
C 14.11/E	615	485	375	282	146	GL90TB	1/4	8,80	220/1/50	293	1,66	12,0
C 13.11/E	862	680	524	392	193	GP12TB	1/3	12,00	220/1/50	390	2,30	13,5
C 38.11/E	937	736	565	422	211	GP14TB	3/8	14,00	220/1/50	440	2,60	18,0
C 12.11/E	1327	1053	807	589	226	GR18TB-T	1/2	18,12	220/1/50	540	3,50	22,0
C 58.11/E	1709	1349	1030	748	289	GR22TB-T	5/8	21,78	220/1/50	670	4,21	26,0
C 34.11/E	1948	1518	1146	829	346	GS26TB-T	3/4	25,95	220/1/50	825	5,00	32,0
C 34.11P/E	2211	1695	1260	901	391	GS30TB-T	3/4	29,93	220/1/50	855	3,90	29,0
C 100.11/E	2320	1913	1536	1212	525	GS34TB-T	1	34,25	220/1/50	1025	4,90	32,0

APPLICAZIONE CAPILLARE A SALDARE

APPLICATION OF CAPILLARY TO BE SOLDERED

ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN

S 16.11/E	324	255	198	149	79	GL45TB	1/6	4,50	220/1/50	185	1,04	8,0
S 15.11/E	403	318	246	186	99	GL60TB	1/5	5,70	220/1/50	218	1,23	8,2
S 14.11L/E	517	408	315	237	122	GL80TB	1/4	7,60	220/1/50	265	1,50	9,7
S 14.11/E	615	485	375	282	146	GL90TB	1/4	8,80	220/1/50	293	1,66	12,0
S 13.11/E	862	680	524	392	193	GP12TB	1/3	12,00	220/1/50	390	2,30	13,5
S 38.11/E	937	736	565	422	211	GP14TB	3/8	14,00	220/1/50	440	2,60	18,0
S 12.11/E	1327	1053	807	589	226	GR18TB-T	1/2	18,12	220/1/50	540	3,50	22,0
S 58.11/E	1709	1349	1030	748	289	GR22TB-T	5/8	21,78	220/1/50	670	4,21	26,0
S 34.11/E	1948	1518	1146	829	346	GS26TB-T	3/4	25,95	220/1/50	825	5,00	32,0
S 34.11P/E	2211	1695	1260	901	391	GS30TB-T	3/4	29,93	220/1/50	855	3,90	29,0
S 100.11/E	2320	1913	1536	1212	525	GS34TB-T	1	34,25	220/1/50	1025	4,90	32,0

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

**R134a MBP/MHBP**



Modello Model Modell	Dimensioni - Dimensions - Abmessungen			Attacchi - Connections - Anschlüsse		
	Larghezza x Profondità x Altezza (mm)			Aspirazione	Liquido	
	Width x Depth x Height (mm)			Suction	Liquid	
	Breite x Tiefe x Höhe (mm)			Ansaugen	Flüssigkeit	
			Peso Weight Gewichte (kg)			
V 15.11/E	300	x 460	x 276	17,0	3/8" - 10	1/4" - 6
V 14.11L/E	300	x 460	x 276	18,0	3/8" - 10	1/4" - 6
V 14.11/E	300	x 460	x 276	18,5	3/8" - 10	1/4" - 6
V 13.11/E	300	x 480	x 276	20,5	3/8" - 10	1/4" - 6
V 38.11/E	300	x 510	x 276	31,5	3/8" - 10	1/4" - 6
V 12.11/E	300	x 540	x 276	24,0	1/2" - 12	1/4" - 6
V 58.11/E	390	x 510	x 350	26,5	1/2" - 12	3/8" - 10
V 34.11/E	390	x 510	x 350	35,0	1/2" - 12	3/8" - 10
V 34.11/E2V	650	x 480	x 330	40,0	1/2" - 12	3/8" - 10
V 34.11P/E	390	x 510	x 350	35,0	1/2" - 12	3/8" - 10
V 34.11P/E2V	650	x 480	x 330	40,0	1/2" - 12	3/8" - 10
V 100.11/E	390	x 540	x 350	39,0	1/2" - 12	3/8" - 10
V 100.11/E2V	650	x 480	x 330	46,0	1/2" - 12	3/8" - 10
C 16.11/E	300	x 420	x 276	14,0	3/8" - 10	1/4" - 6
C 15.11/E	300	x 420	x 276	16,3	3/8" - 10	1/4" - 6
C 14.11L/E	300	x 420	x 276	17,3	3/8" - 10	1/4" - 6
C 14.11/E	300	x 460	x 276	17,8	3/8" - 10	1/4" - 6
C 13.11/E	300	x 460	x 276	19,7	3/8" - 10	1/4" - 6
C 38.11/E	300	x 480	x 276	30,7	3/8" - 10	1/4" - 6
C 12.11/E	300	x 510	x 276	23,2	1/2" - 12	1/4" - 6
C 58.11/E	390	x 480	x 350	25,1	1/2" - 12	3/8" - 10
C 34.11/E	390	x 480	x 350	33,6	1/2" - 12	3/8" - 10
C 34.11P/E	390	x 480	x 350	33,6	1/2" - 12	3/8" - 10
C 100.11/E	390	x 510	x 350	37,6	1/2" - 12	3/8" - 10
S 16.11/E	300	x 390	x 276	13,6	8	6
S 15.11/E	300	x 390	x 276	15,9	8	6
S 14.11L/E	300	x 390	x 276	16,9	8	6
S 14.11/E	300	x 390	x 276	17,4	8	6
S 13.11/E	300	x 390	x 276	19,3	8	6
S 38.11/E	300	x 480	x 276	30,3	8	6
S 12.11/E	300	x 510	x 276	22,8	10	6
S 58.11/E	390	x 480	x 350	24,6	12	8
S 34.11/E	390	x 480	x 350	33,1	12	8
S 34.11P/E	390	x 480	x 350	33,1	12	8
S 100.11/E	390	x 510	x 350	37,1	12	8