



**CON COMPRESSORE L' UNITE' HERMETIQUE**  
**WITH L' UNITE' HERMETIQUE COMPRESSOR**  
**MIT L' UNITE' HERMETIQUE KOMPRESSOR**

**R404A LBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	-10°C	-20°C	-25°C	-30°C	-35°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistungsaufn. (W)	FLA (A)	LRA (A)

**APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI**

**APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES**

**ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN**

V 14.13	506	319	244	184	138	AEZ2415Z	1/4	8,10	220/1/50	368	2,22	14
V 13.13	636	414	314	222	139	CAE2417Z	1/3	11,30	220/1/50	406	1,97	13,1
V 38.13	742	487	378	282	200	CAE2420Z	3/8	12,50	220/1/50	519	3,21	18
V 12.13	855	583	462	351	251	CAE2424Z	1/2	15,00	220/1/50	630	2,55	17
TV 12.13	904	566	427	308	212	TAJ2428Z	1/2	15,20	380/3/50	573	1,11	9,4
V 34.13	1115	709	540	395	275	CAJ2432Z	3/4	18,30	220/1/50	671	2,70	21
V 34.13/2V	1115	709	540	395	275	CAJ2432Z	3/4	18,30	220/1/50	767	2,70	21
V 120.13	1640	1053	815	616	458	CAJ2446Z	1,2	26,15	220/1/50	1012	4,00	29
V 120.13/2V	1640	1053	815	616	458	CAJ2446Z	1,2	26,15	220/1/50	967	4,00	29
TV 120.13	1640	1053	815	616	458	TAJ2446Z	1,2	26,15	380/3/50	1000	1,47	13
TV 120.13/2V	1640	1053	815	616	458	TAJ2446Z	1,2	26,15	380/3/50	955	1,47	13
V 150.13	2156	1412	1101	834	612	CAJ2464Z	1,5	34,45	220/1/50	1378	5,50	38
V 150.13/2V	2156	1412	1101	834	612	CAJ2464Z	1,5	34,45	220/1/50	1364	5,50	38
TV 150.13	2156	1412	1101	834	612	TAJ2464Z	1,5	34,45	380/3/50	1379	2,04	16
TV 150.13/2V	2156	1412	1101	834	612	TAJ2464Z	1,5	34,45	380/3/50	1365	2,04	16
TV 200.13	3237	1975	1462	1018	639	TFH2480Z	2	53,20	380/3/50	1831	2,81	23
TV 200.13/2V	3237	1975	1462	1018	639	TFH2480Z	2	53,20	380/3/50	1951	2,81	23
TV 300.13	4485	2820	2156	1611	1188	TFH2511Z	3	74,30	380/3/50	2196	3,53	28
TV 300.13/2V	4485	2820	2156	1611	1188	TFH2511Z	3	74,30	380/3/50	2311	3,53	28
TV 500.13/2V	6455	3971	2975	2151	1506	TAG2516Z	5	112,5	380/3/50	3223	4,88	46
TV 700.13/2V	7906	4972	3792	2814	2046	TAG2522Z	7	134,8	380/3/50	3910	6,42	56

**APPLICAZIONE CAPILLARE CON RUBINETTI**

**APPLICATION OF CAPILLARY WITH SHUT OFF VALVES**

**ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN**

C 14.13	506	319	244	184	138	AEZ2415Z	1/4	8,10	220/1/50	368	2,22	14
C 13.13	636	414	314	222	139	CAE2417Z	1/3	11,30	220/1/50	406	1,97	13,1
C 38.13	742	487	378	282	200	CAE2420Z	3/8	12,50	220/1/50	519	3,21	18
C 12.13	855	583	462	351	251	CAE2424Z	1/2	15,00	220/1/50	630	2,55	17
C 34.13	1115	709	540	395	275	CAJ2432Z	3/4	18,30	220/1/50	573	1,11	9,4
C 120.13	1640	1053	815	616	458	CAJ2446Z	1,2	26,15	220/1/50	671	4,00	29
C 150.13	2156	1412	1101	834	612	CAJ2464Z	1,5	34,45	220/1/50	1378	5,50	38

**APPLICAZIONE CAPILLARE A SILDARE**

**APPLICATION OF CAPILLARY TO BE SOLDERED**

**ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN**

S 14.13	506	319	244	184	138	AEZ2415Z	1/4	8,10	220/1/50	368	2,22	14
S 13.13	636	414	314	222	139	CAE2417Z	1/3	11,30	220/1/50	406	1,97	13,1
S 38.13	742	487	378	282	200	CAE2420Z	3/8	12,50	220/1/50	519	3,21	18
S 12.13	855	583	462	351	251	CAE2424Z	1/2	15,00	220/1/50	630	2,55	17
S 34.13	1115	709	540	395	275	CAJ2432Z	3/4	18,30	220/1/50	573	1,11	9,4
S 120.13	1640	1053	815	616	458	CAJ2446Z	1,2	26,15	220/1/50	671	4,00	29
S 150.13	2156	1412	1101	834	612	CAJ2464Z	1,5	34,45	220/1/50	1378	5,50	38

CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R404A LBP**



DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen			Attacchi - Connections - Anschlüsse		
	Larghezza x Profondità x Altezza (mm)			Aspirazione Suction Ansaugen	Liquido Liquid Flüssigkeit	
	Width x Depth x Height (mm)					
	Breite x Tiefe x Höhe (mm)					
Peso Weight Gewichte			(kg)			
V 14.13	300 x 460 x 276			20,0	3/8" - 10	1/4" - 6
V 13.13	300 x 480 x 276			20,8	3/8" - 10	1/4" - 6
V 38.13	300 x 510 x 276			28,5	3/8" - 10	1/4" - 6
V 12.13	300 x 540 x 276			28,5	3/8" - 10	1/4" - 6
TV 12.13	390 x 480 x 350			28,7	1/2" - 12	1/4" - 6
V 34.13	390 x 480 x 350			28,2	1/2" - 12	1/4" - 6
V 34.13/2V	650 x 480 x 276			34,2	1/2" - 12	1/4" - 6
V 120.13	390 x 510 x 350			34,2	1/2" - 12	3/8" - 10
V 120.13/2V	650 x 480 x 330			34,2	1/2" - 12	3/8" - 10
TV 120.13	390 x 510 x 350			31,8	1/2" - 12	3/8" - 10
TV 120.13/2V	650 x 480 x 330			33,0	1/2" - 12	3/8" - 10
V 150.13	450 x 540 x 375			41,9	5/8" - 16	3/8" - 10
V 150.13/2V	650 x 480 x 330			48,5	5/8" - 16	3/8" - 10
TV 150.13	450 x 540 x 375			38,9	5/8" - 16	3/8" - 10
TV 150.13/2V	650 x 480 x 330			46,0	5/8" - 16	3/8" - 10
TV 200.13	520 x 580 x 440			50,5	5/8" - 16	3/8" - 10
TV 200.13/2V	790 x 580 x 420			54,0	5/8" - 16	3/8" - 10
TV 300.13	750 x 650 x 560			50,5	5/8" - 16	3/8" - 10
TV 300.13/2V	790 x 580 x 420			54,0	5/8" - 16	3/8" - 10
TV 500.13/2V	940 x 650 x 465			80,0	7/8" - 22	1/2" - 12
TV 700.13/2V	940 x 650 x 565			80,0	1.1/8" - 28	5/8" - 16
C 14.13	300 x 460 x 276			19,3	3/8" - 10	1/4" - 6
C 13.13	300 x 460 x 276			20,0	3/8" - 10	1/4" - 6
C 38.13	300 x 480 x 276			27,7	3/8" - 10	1/4" - 6
C 12.13	300 x 510 x 276			27,7	3/8" - 10	1/4" - 6
C 34.13	390 x 480 x 350			27,4	1/2" - 12	1/4" - 6
C 120.13	390 x 480 x 350			32,8	1/2" - 12	3/8" - 10
C 150.13	450 x 540 x 375			40,5	5/8" - 16	3/8" - 10
S 14.13	300 x 390 x 276			18,9	8	6
S 13.13	300 x 390 x 276			19,6	8	6
S 38.13	300 x 420 x 276			27,3	8	6
S 12.13	300 x 510 x 276			27,3	8	6
S 34.13	390 x 480 x 350			26,9	12	6
S 120.13	390 x 480 x 350			32,3	12	8
S 150.13	450 x 540 x 375			40,0	16	8