



CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

R404A LBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	-10°C	-20°C	-25°C	-30°C	-40°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm ³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

V 15.13/E	332	204	155	115	58	ML60FB	1/5	6,00	220/1/50	300	1,60	9,8
V 14.13/E	533	330	251	186	92	ML90FB	1/4	8,80	220/1/50	390	2,30	12,2
V 13.13/E	730	437	324	231	98	MP12FB	1/3	12,00	220/1/50	490	2,75	14,8
V 12.13/E	821	497	371	266	116	MP14FB	1/2	14,00	220/1/50	630	3,40	17,5
V 34.13/E	1168	666	476	322	110	MR18FB-T	3/4	18,20	220/1/50	669	2,76	18,0
V 100.13L/E	1387	810	589	407	150	MR22FB-T	1	21,78	220/1/50	805	3,50	24,0
V 100.13L/E2V	1387	810	589	407	150	MR22FB-T	1	21,78	220/1/50	815	3,50	24,0
V 120.13/E	1671	1005	743	523	196	MS26FB-T	1,2	26,15	220/1/50	1015	4,50	30,0
V 120.13/E2V	1671	1005	743	523	196	MS26FB-T	1,2	26,15	220/1/50	970	4,50	30,0
V 150.13/E	2189	1316	972	683	254	MS34FB-T	1,5	34,25	220/1/50	1385	6,40	39,0
V 150.13/E2V	2189	1316	972	683	254	MS34FB-T	1,5	34,25	220/1/50	1371	6,40	39,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

C 15.13/E	332	204	155	115	58	ML60FB	1/5	6,00	220/1/50	300	1,60	9,8
C 14.13/E	533	330	251	186	92	ML90FB	1/4	8,80	220/1/50	390	2,30	12,2
C 13.13/E	730	437	324	231	98	MP12FB	1/3	12,00	220/1/50	490	2,75	14,8
C 12.13/E	821	497	371	266	116	MP14FB	1/2	14,00	220/1/50	630	3,40	17,5
C 34.13/E	1168	666	476	322	110	MR18FB-T	3/4	18,20	220/1/50	669	2,76	18,0
C 100.13L/E	1387	810	589	407	150	MR22FB-T	1	21,78	220/1/50	805	3,50	24,0
C 120.13/E	1671	1005	743	523	196	MS26FB-T	1,2	26,15	220/1/50	1015	4,50	30,0
C 150.13/E	2189	1316	972	683	254	MS34FB-T	1,5	34,25	220/1/50	1385	6,40	39,0

APPLICAZIONE CAPILLARE A SALDARE

APPLICATION OF CAPILLARY TO BE SOLDERED

ANWENDUNG KAPILLARROHR ZUM ANSCHWEIßEN

S 15.13/E	332	204	155	115	58	ML60FB	1/5	6,00	220/1/50	300	1,60	9,8
S 14.13/E	533	330	251	186	92	ML90FB	1/4	8,80	220/1/50	390	2,30	12,2
S 13.13/E	730	437	324	231	98	MP12FB	1/3	12,00	220/1/50	490	2,75	14,8
S 12.13/E	821	497	371	266	116	MP14FB	1/2	14,00	220/1/50	630	3,40	17,5
S 34.13/E	1168	666	476	322	110	MR18FB-T	3/4	18,20	220/1/50	669	2,76	18,0
S 100.13L/E	1387	810	589	407	150	MR22FB-T	1	21,78	220/1/50	805	3,50	24,0
S 120.13/E	1671	1005	743	523	196	MS26FB-T	1,2	26,15	220/1/50	1015	4,50	30,0
S 150.13/E	2189	1316	972	683	254	MS34FB-T	1,5	34,25	220/1/50	1385	6,40	39,0

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

R404A LBP



Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse	
			Aspirazione	Liquido
			Suction	Liquid
			Ansaugen	Flüssigkeit
V 15.13/E	300 x 460 x 276	20,0	3/8" - 10	1/4" - 6
V 14.13/E	300 x 460 x 276	20,0	3/8" - 10	1/4" - 6
V 13.13/E	300 x 510 x 276	21,0	3/8" - 10	1/4" - 6
V 12.13/E	300 x 540 x 276	26,0	3/8" - 10	1/4" - 6
V 34.13/E	390 x 480 x 350	26,5	1/2" - 12	1/4" - 6
V 100.13L/E	390 x 480 x 350	27,0	1/2" - 12	3/8" - 10
V 100.13L/E2V	650 x 480 x 276	34,2	1/2" - 12	3/8" - 10
V 120.13/E	390 x 510 x 350	34,2	1/2" - 12	3/8" - 10
V 120.13/E2V	650 x 480 x 330	48,5	1/2" - 12	3/8" - 10
V 150.13/E	450 x 450 x 375	41,0	1/2" - 12	3/8" - 10
V 150.13/E2V	650 x 480 x 330	48,5	1/2" - 12	3/8" - 10
C 15.13/E	300 x 420 x 276	19,3	3/8" - 10	1/4" - 6
C 14.13/E	300 x 420 x 276	19,3	3/8" - 10	1/4" - 6
C 13.13/E	300 x 480 x 276	20,2	3/8" - 10	1/4" - 6
C 12.13/E	300 x 510 x 276	25,2	3/8" - 10	1/4" - 6
C 34.13/E	390 x 480 x 350	25,7	1/2" - 12	1/4" - 6
C 100.13L/E	390 x 480 x 350	25,6	1/2" - 12	3/8" - 10
C 120.13/E	390 x 480 x 350	32,8	1/2" - 12	3/8" - 10
C 150.13/E	450 x 450 x 375	39,6	1/2" - 12	3/8" - 10
S 15.13/E	300 x 390 x 276	18,9	8	6
S 14.13/E	300 x 390 x 276	18,9	8	6
S 13.13/E	300 x 420 x 276	19,8	8	6
S 12.13/E	300 x 480 x 276	24,8	10	6
S 34.13/E	390 x 480 x 350	25,3	10	6
S 100.13L/E	390 x 480 x 350	25,2	10	6
S 120.13/E	390 x 480 x 350	32,3	12	6
S 150.13/E	450 x 450 x 375	39,1	12	8