

CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R404A - R507 MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-25°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 15.3	617	490	<b>383</b>	292		AEZ4425Z	1/5	4,50	220/1/50	259	1,49	9
WV 14.3L	788	632	<b>498</b>	385		AEZ4430Z	1/4	5,70	220/1/50	316	1,92	11
WV 14.3	1059	850	<b>673</b>	528		AEZ4440Z	1/4	7,55	220/1/50	388	2,13	18
WV 13.3	1324	1051	<b>824</b>	642		CAE4450Z	1/3	9,40	220/1/50	486	3,06	16
WV 12.3	1633	1309	<b>1032</b>	802	477	CAE9460Z	1/2	11,30	220/1/50	505	2,49	17
WV 58.3	1986	1595	<b>1263</b>	989	608	CAE9470Z	5/8	13,30	220/1/50	629	2,92	20
WV 34.3	2306	1859	<b>1478</b>	1156	664	CAJ9480Z	3/4	15,20	220/1/50	713	2,91	22
TWV 34.3	2306	1859	<b>1478</b>	1156	664	TAJ9480Z	3/4	15,20	380/3/50	713	1,41	13
WV 100.3	2828	2283	<b>1814</b>	1421	851	CAJ9510Z	1	18,30	220/1/50	831	3,60	29
TWV 100.3	2828	2283	<b>1814</b>	1421	851	TAJ9510Z	1	18,30	380/3/50	830	1,59	13
WV 110.3	3575	2837	<b>2210</b>	1681	873	CAJ9513Z	1,1	24,0	220/1/50	1025	4,31	30
TWV 110.3	3575	2837	<b>2210</b>	1681	873	TAJ9513Z	1,1	24,0	380/3/50	1025	1,76	13
WV 120.3	4077	3268	<b>2582</b>	2016	1232	CAJ4517Z	1,2	25,95	220/1/50	1104	5,01	32
TWV 120.3	4077	3268	<b>2582</b>	2016	1232	TAJ4517Z	1,2	25,95	380/3/50	1157	2,38	18
WV 150.3	5369	4319	<b>3405</b>	2625		CAJ4519Z	1,5	34,45	220/1/50	1544	6,91	31
TWV 150.3	5369	4319	<b>3405</b>	2625		TAJ4519Z	1,5	34,45	380/3/50	1473	3,04	22
WV 200.3	5943	4668	<b>3605</b>	2720		FH4524Z	2	43,50	220/1/50	1693	7,44	49
TWV 200.3	5943	4668	<b>3605</b>	2720		TFH4524Z	2	43,50	380/3/50	1682	3,43	24

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 15.3	617	490	<b>383</b>	292		AEZ4425Z	1/5	4,50	220/1/50	259	1,49	9
WC 14.3L	788	632	<b>498</b>	385		AEZ4430Z	1/4	5,70	220/1/50	316	1,92	11
WC 14.3	1059	850	<b>673</b>	528		AEZ4440Z	1/4	7,55	220/1/50	388	2,13	18
WC 13.3	1324	1051	<b>824</b>	642		CAE4450Z	1/3	9,40	220/1/50	486	3,06	16
WC 12.3	1633	1309	<b>1032</b>	802	477	CAE9460Z	1/2	11,30	220/1/50	505	2,49	17
WC 58.3	1986	1595	<b>1263</b>	989	608	CAE9470Z	5/8	13,30	220/1/50	629	2,92	20
WC 34.3	2306	1859	<b>1478</b>	1156	664	CAJ9480Z	3/4	15,20	220/1/50	713	2,91	22
WC 100.3	2828	2283	<b>1814</b>	1421	851	CAJ9510Z	1	18,30	220/1/50	831	3,60	29
WC 110.3	3575	2837	<b>2210</b>	1681	873	CAJ9513Z	1,1	24,0	220/1/50	1025	4,31	30
WC 120.3	4077	3268	<b>2582</b>	2016	1232	CAJ4517Z	1,2	25,95	220/1/50	1544	5,01	32



CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R404A - R507 MBP/MHBP**

DIMENSIONI - PESI - ATTACCHI  
 DIMENSIONS - WEIGHT - CONNECTIONS  
 ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 15.3	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3L	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.3	300 x 480 x 250	22,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.3	300 x 510 x 365	26,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 58.3	300 x 510 x 365	34,6	3/8" - 10	1/4" - 6	3/8" FPT
WV 34.3	390 x 480 x 285	31,5	1/2" - 12	3/8" - 10	3/8" FPT
TWV 34.3	390 x 480 x 285	31,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 100.3	390 x 480 x 285	34,8	5/8" - 16	3/8" - 10	3/8" FPT
TWV 100.3	390 x 480 x 285	34,8	5/8" - 16	3/8" - 10	3/8" FPT
WV 110.3	390 x 480 x 350	35,3	5/8" - 16	3/8" - 10	3/8" FPT
TWV 110.3	390 x 480 x 350	35,1	5/8" - 16	3/8" - 10	3/8" FPT
WV 120.3	390 x 480 x 350	35,3	5/8" - 16	3/8" - 10	3/8" FPT
TWV 120.3	390 x 480 x 350	36,5	5/8" - 16	3/8" - 10	3/8" FPT
WV 150.3	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT
TWV 150.3	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT
WV 200.3	540 x 450 x 390	40,5	5/8" - 16	3/8" - 10	1/2" FPT
TWV 200.3	540 x 450 x 390	40,5	5/8" - 16	3/8" - 10	1/2" FPT
WC 15.3	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3L	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.3	300 x 510 x 365	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.3	300 x 510 x 365	31,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 58.3	390 x 480 x 285	34,8	1/2" - 12	3/8" - 10	3/8" FPT
WC 34.3	390 x 480 x 285	30,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 100.3	390 x 480 x 285	30,5	5/8" - 16	3/8" - 10	3/8" FPT
WC 110.3	390 x 480 x 350	34,0	5/8" - 16	3/8" - 10	3/8" FPT
WC 120.3	390 x 480 x 350	34,0	5/8" - 16	3/8" - 10	3/8" FPT

