

CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R404A - R507 MBP/MHBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-20°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 15.3/A	548	452	367	295	234	NB6144GK	1/5	4,51	220/1/50	255	1,80	15,3
WV 14.3L/A	756	623	508	412	332	NB6165GK	1/4	6,06	220/1/50	356	2,38	13,8
WV 14.3/A	943	760	601	465	352	NE6181GK	1/4	7,38	220/1/50	339	2,30	16,5
WV 13.3/A	1212	1000	820	669	551	NE6210GK	1/3	8,79	220/1/50	420	2,50	13,8
WV 12.3/A	1596	1345	1137	966	825	NE9213GK	1/2	12,10	220/1/50	644	4,02	14,1
WV 34.3/A	1869	1540	1240	967	721	T6217GK	3/4	14,51	220/1/50	708	4,07	22,0
WV 100.3/A	2058	1697	1280	1106	875	T6220GK	1	17,40	220/1/50	713	4,23	26,5
WV 110.3/A	3006	2446	1960	1550	1216	NJ9226GK	1,1	21,70	220/1/50	915	3,86	27,5
TWV 110.3/A	3006	2446	1960	1550	1216	NJ9226GS	1,1	21,70	380/3/50	915	1,61	10,0
WV 120.3/A	3700	3081	2400	1894	1484	NJ9232GK	1,2	26,14	220/1/50	1065	4,88	33,7
TWV 120.3/A	3700	3081	2400	1894	1484	NJ9232GS	1,2	26,14	380/3/50	1074	1,99	13,0
WV 150.3/A	4566	3789	3090	2469	1926	NJ9238GK	1,5	32,70	220/1/50	1428	6,53	43,0
TWV 150.3/A	4566	3789	3090	2469	1926	NJ9238GS	1,5	32,70	380/3/50	1290	2,76	22,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 15.3/A	548	452	367	295	234	NB6144GK	1/5	4,51	220/1/50	255	1,80	15,3
WC 14.3L/A	756	623	508	412	332	NB6165GK	1/4	6,06	220/1/50	356	2,38	13,8
WC 14.3/A	943	760	601	465	352	NE6181GK	1/4	7,38	220/1/50	339	2,30	16,5
WC 13.3/A	1212	1000	820	669	551	NE6210GK	1/3	8,79	220/1/50	420	2,50	13,8
WC 12.3/A	1596	1345	1137	966	825	NE9213GK	1/2	12,10	220/1/50	644	4,02	14,1
WC 34.3/A	1869	1540	1240	967	721	T6217GK	3/4	14,51	220/1/50	708	4,07	22,0
WC 100.3/A	2058	1697	1280	1106	875	T6220GK	1	17,40	220/1/50	713	4,23	26,5
WC 110.3/A	3006	2446	1960	1550	1216	NJ9226GK	1,1	21,70	220/1/50	915	3,86	27,5
WC 120.3/A	3700	3081	2400	1894	1484	NJ9232GK	1,2	26,14	220/1/50	1065	4,88	33,7



CON COMPRESSORE **EMBRACO - ASPERA**
 WITH **EMBRACO - ASPERA** COMPRESSOR
 MIT **EMBRACO - ASPERA** KOMPRESSOR

R404A - R507 MBP/MHBP

DIMENSIONI - PESI - ATTACCHI
DIMENSIONS - WEIGHT - CONNECTIONS
ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 15.3/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3L/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.3/A	300 x 480 x 250	22,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.3/A	300 x 510 x 265	26,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 34.3/A	390 x 480 x 265	31,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 100.3/A	390 x 480 x 265	34,8	1/2" - 12	3/8" - 10	3/8" FPT
WV 110.3/A	390 x 480 x 350	35,3	1/2" - 12	3/8" - 10	3/8" FPT
TWV 110.3/A	390 x 480 x 350	35,1	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.3/A	390 x 480 x 350	35,3	5/8" - 16	3/8" - 10	3/8" FPT
TWV 120.3/A	390 x 480 x 350	36,5	5/8" - 16	3/8" - 10	3/8" FPT
WV 150.3/A	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT
TWV 150.3/A	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT
WC 15.3/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3L/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.3/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.3/A	300 x 510 x 265	31,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 34.3/A	390 x 480 x 265	31,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 100.3/A	390 x 480 x 265	30,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 110.3/A	390 x 480 x 350	34,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.3/A	390 x 480 x 350	34,0	5/8" - 16	3/8" - 10	3/8" FPT

