

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

R404A - R507 MBP/MHBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-25°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 15.3/E	633	514	412	324	189	ML45TB	1/5	4,50	220/1/50	282	1,57	9,5
WV 14.3L/E	770	623	496	387	219	ML60TB	1/4	5,70	220/1/50	318	1,75	10,6
WV 14.3/E	1068	865	689	538	296	ML80TB	1/4	7,60	220/1/50	408	2,29	12,8
WV 13.3/E	1247	1010	806	630	359	ML90TB	1/3	8,80	220/1/50	480	2,79	16,0
WV 12.3/E	1727	1404	1122	880	505	MP12TB	1/2	12,00	220/1/50	570	2,61	17,0
WV 58.3/E	2004	1642	1328	1052	616	MP14TB	5/8	14,00	220/1/50	696	3,15	19,0
WV 34.3/E	2251	1821	1450	1128	625	MR16TB	3/4	15,00	220/1/50	736	3,7	23,0
WV 100.3/E	2571	2068	1630	1253	664	MR18TB	1	18,00	220/1/50	786	4,08	29,5
WV 110.3/E	3152	2531	1993	1533	821	MR22TB	1,1	21,00	220/1/50	914	4,59	32,0
WV 120.3/E	3832	3105	2473	1926	1064	MS26TB	1,2	25,00	220/1/50	1091	5,49	38,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 15.3/E	633	514	412	324	189	ML45TB	1/5	4,50	220/1/50	282	1,57	9,5
WC 14.3L/E	770	623	496	387	219	ML60TB	1/4	5,70	220/1/50	318	1,75	10,6
WC 14.3/E	1068	865	689	538	296	ML80TB	1/4	7,60	220/1/50	408	2,29	12,8
WC 13.3/E	1247	1010	806	630	359	ML90TB	1/3	8,80	220/1/50	480	2,79	16,0
WC 12.3/E	1727	1404	1122	880	505	MP12TB	1/2	12,00	220/1/50	570	2,61	17,0
WC 58.3/E	2004	1642	1328	1052	616	MP14TB	5/8	14,00	220/1/50	696	3,15	19,0
WC 34.3/E	2251	1821	1450	1128	625	MR16TB	3/4	15,00	220/1/50	736	3,7	23,0
WC 100.3/E	2571	2068	1630	1253	664	MR18TB	1	18,00	220/1/50	786	4,08	29,5
WC 110.3/E	3152	2531	1993	1533	821	MR22TB	1,1	21,00	220/1/50	914	4,59	32,0
WC 120.3/E	3832	3105	2473	1926	1064	MS26TB	1,2	25,00	220/1/50	1091	5,49	38,0



CON COMPRESSORE **ACC** (ex Electrolux)

WITH **ACC** (ex Electrolux) COMPRESSOR

MIT **ACC** (ex Electrolux) KOMPRESSOR

R404A - R507 MBP/MHBP

DIMENSIONI - PESI - ATTACCHI

DIMENSIONS - WEIGHT - CONNECTIONS

ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 15.3/E	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3L/E	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.3/E	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.3/E	300 x 480 x 250	22,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.3/E	300 x 510 x 265	26,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 58.3/E	300 x 510 x 265	34,6	3/8" - 10	1/4" - 6	3/8" FPT
WV 34.3/E	390 x 480 x 265	31,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 100.3/E	390 x 480 x 265	34,8	1/2" - 12	3/8" - 10	3/8" FPT
WV 110.3/E	390 x 480 x 350	35,3	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.3/E	390 x 480 x 350	35,3	5/8" - 16	3/8" - 10	3/8" FPT
WC 15.3/E	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3L/E	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.3/E	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.3/E	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.3/E	300 x 510 x 265	31,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 58.3/E	300 x 510 x 265	34,8	3/8" - 10	1/4" - 6	3/8" FPT
WC 34.3/E	390 x 480 x 265	31,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 100.3/E	390 x 480 x 265	30,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 110.3/E	390 x 480 x 350	34,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.3/E	390 x 480 x 350	34,0	5/8" - 16	3/8" - 10	3/8" FPT

