

CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R 22 MBP/MHBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-20°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 15.5	537	434	<b>347</b>	270		AEZ4425E	1/5	4,50	220/1/50	282	1,53	9
WV 14.5L	698	567	<b>455</b>	360		AEZ4430E	1/4	5,70	220/1/50	342	1,91	11
WV 14.5	913	775	<b>628</b>	509		AEZ4440E	1/4	7,55	220/1/50	417	2,20	18
WV 13.5	1162	938	<b>751</b>	600		CAE4450E	1/3	9,40	220/1/50	512	2,79	15
WV 12.5	1410	1198	<b>970</b>	783	635	CAE9460T	1/2	11,30	220/1/50	592	2,71	15,2
WV 58.5	2055	1684	<b>1370</b>	1111	842	CAJ9480T	5/8	15,20	220/1/50	721	3,15	22
TWV 58.5	2055	1684	<b>1370</b>	1111	842	TAJ9480T	5/8	15,20	380/3/50	752	1,43	13
WV 100.5L	2475	2040	<b>1665</b>	1350	1091	CAJ9510T	1	18,30	220/1/50	884	4,07	29
TWV 100.5L	2475	2040	<b>1665</b>	1350	1091	TAJ9510T	1	18,30	380/3/50	903	1,58	13
WV 110.5	3127	2503	<b>1966</b>	1512	1144	CAJ9513T	1,1	24,20	220/1/50	1075	5,07	30
TWV 110.5	3127	2503	<b>1966</b>	1512	1144	TAJ9513T	1,1	24,20	380/3/50	1065	1,92	13
WV 120.5	3538	2863	<b>2265</b>	1735		CAJ4517E	1,2	25,95	220/1/50	1173	5,27	35
TWV 120.5	3538	2863	<b>2265</b>	1735		TAJ4517E	1,2	25,95	380/3/50	1214	2,08	18
TWV 150.5	4671	3841	<b>3120</b>	2505		TAJ4519T	1,5	34,45	380/3/50	1569	3,04	22
WV 200.5	5359	4249	<b>3327</b>	2589		FH4524F	2	43,50	220/1/50	1864	8,21	51
TWV 200.5	5359	4249	<b>3327</b>	2589		TFH4524F	2	43,50	380/3/50	1854	3,29	24

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 15.5	537	434	<b>347</b>	270		AEZ4425E	1/5	4,50	220/1/50	282	1,53	9
WC 14.5L	698	567	<b>455</b>	360		AEZ4430E	1/4	5,70	220/1/50	342	1,91	11
WC 14.5	913	775	<b>628</b>	509		AEZ4440E	1/4	7,55	220/1/50	417	2,20	18
WC 13.5	1162	938	<b>751</b>	600		CAE4450E	1/3	9,40	220/1/50	512	2,79	15
WC 12.5	1410	1198	<b>970</b>	783	635	CAE9460T	1/2	11,30	220/1/50	592	2,71	15,2
WC 58.5	2055	1684	<b>1370</b>	1111	842	CAJ9480T	5/8	15,20	220/1/50	721	1,43	13
WC 100.5L	2475	2040	<b>1665</b>	1350	1091	CAJ9510T	1	18,30	220/1/50	884	4,07	29
WC 110.5	3127	2503	<b>1966</b>	1512	1144	CAJ9513T	1,1	24,20	220/1/50	1075	2,07	30
WC 120.5	3538	2863	<b>2265</b>	1735		CAJ4517E	1,2	25,95	220/1/50	1173	5,27	35



CON COMPRESSORE L' UNITE' HERMETIQUE  
**WITH L' UNITE' HERMETIQUE COMPRESSOR**  
**MIT L' UNITE' HERMETIQUE KOMPRESSOR**

**R 22 MBP/MHBP**

**DIMENSIONI - PESI - ATTACCHI**  
**DIMENSIONS - WEIGHT - CONNECTIONS**  
**ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE**

Modello Model Modell	Dimensioni - Dimensions - Abmessungen			Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
	Larghezza x Profondità x Altezza (mm)			Aspirazione Suction Ansaugen	Liquido Liquid Flüssigkeit	
	Width x Depth x Height (mm)					
	Breite x Tiefe x Höhe (mm)			Peso Weight Gewichte (kg)		
WV 15.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WV 14.5L	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WV 14.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WV 13.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WV 12.5	300 x 510 x 265			1/2" - 12	1/4" - 6	3/8" FPT
WV 58.5	390 x 480 x 285			1/2" - 12	3/8" - 10	3/8" FPT
TWV 58.5	390 x 480 x 285			1/2" - 12	3/8" - 10	3/8" FPT
WV 100.5L	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
TWV 100.5L	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
WV 110.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
TWV 110.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
WV 120.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
TWV 120.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
TWV 150.5	540 x 450 x 360			5/8" - 16	3/8" - 10	1/2" FPT
WV 200.5	540 x 450 x 360			5/8" - 16	3/8" - 10	1/2" FPT
TWV 200.5	540 x 450 x 360			5/8" - 16	3/8" - 10	1/2" FPT
WC 15.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WC 14.5L	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WC 14.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WC 13.5	300 x 480 x 250			3/8" - 10	1/4" - 6	3/8" FPT
WC 12.5	300 x 510 x 265			1/2" - 12	1/4" - 6	3/8" FPT
WC 58.5	390 x 480 x 285			1/2" - 12	3/8" - 10	3/8" FPT
WC 100.5L	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
WC 110.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT
WC 120.5	390 x 480 x 285			5/8" - 16	3/8" - 10	3/8" FPT

