

CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R 22 MBP/MHBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	-20°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm ³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 16.5/A	474	388	314	251		NB6144E	1/6	4,38	220/1/50	242	1,64	15,3
WV 15.5/A	543	445	364	295		NB6152E	1/5	4,85	220/1/50	277	1,66	15,3
WV 14.5L/A	661	544	444	362		NB6165E	1/4	6,00	220/1/50	319	2,11	13,8
WV 14.5/A	820	660	526	421		NB6181E	1/4	7,40	220/1/50	320	2,04	16,5
WV 13.5/A	972	784	628	505		NE6210E	1/3	8,90	220/1/50	393	2,25	13,8
WV 12.5/A	1383	1123	896	702	542	NE9213E	1/2	12,00	220/1/50	501	2,17	16,0
WV 58.5L/A	1674	1334	1018	726		T6217E	5/8	14,50	220/1/50	634	3,79	18,0
WV 34.5/A	1844	1511	1175	836		T6220E	3/4	17,40	220/1/50	670	3,96	20,0
WV 100.5L/A	2546	2065	1645	1286	987	NJ9226E	1	21,70	220/1/50	792	3,34	27,5
TWV 100.5L/A	2546	2065	1645	1286	987	NJ9226P	1	21,70	380/1/50	805	1,41	10,0
WV 110.5/A						J7228F/B	1,1	23,80	220/1/50	959	4,2	30,5
TWV 110.5/A						J7228P	1,1	23,80	380/1/50	934	1,89	11,5
WV 120.5/A	2807	2297	1856	1470	1128	NJ9232E	1,2	26,20	220/1/50	952	4,21	33,7
TWV 120.5/A	2807	2297	1856	1470	1128	NJ9232P	1,2	26,20	380/1/50	957	2,01	13,0
WV 130.5/A	3678	2973	2370	1868	1468	NJ9238E	1,3	32,70	220/1/50	1292	5,71	43,0
TWV 130.5/A	3678	2973	2370	1868	1468	NJ9238P	1,3	32,70	380/1/50	1292	3,13	22,0
WV 150.5/A						J7240F/B	1,5	34,37	220/1/50	1475	6,65	45,2
TWV 150.5/A						J7240P	1,5	34,37	380/1/50	1475	3,65	23,1

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 16.5/A	474	388	314	251		NB6144E	1/6	4,38	220/1/50	242	1,64	15,3
WC 15.5/A	543	445	364	295		NB6152E	1/5	4,85	220/1/50	277	1,66	15,3
WC 14.5L/A	661	544	444	362		NB6165E	1/4	6,00	220/1/50	319	2,11	13,8
WC 14.5/A	820	660	526	421		NB6181E	1/4	7,40	220/1/50	320	2,04	16,5
WC 13.5/A	972	784	628	505		NE6210E	1/3	8,90	220/1/50	393	2,25	13,8
WC 12.5/A	1383	1123	896	702	542	NE9213E	1/2	12,00	220/1/50	501	2,17	16,0
WC 58.5L/A	1674	1334	1018	726		T6217E	5/8	14,50	220/1/50	634	3,79	18,0
WC 34.5/A	1844	1511	1175	836		T6220E	3/4	17,40	220/1/50	670	3,96	20,0
WC 100.5L/A	2546	2065	1645	1286	987	NJ9226E	1	21,70	220/1/50	792	3,34	27,5
WC 110.5/A						J7228F/B	1,1	23,80	220/1/50	959	4,2	30,5
WC 120.5/A	2807	2297	1856	1470	1128	NJ9232E	1,2	26,20	220/1/50	952	4,21	33,7
WC 130.5/A	3678	2973	2370	1868	1468	NJ9238E	1,3	32,70	220/1/50	1475	6,65	45,2
WC 150.5/A						J7240P	1,5	34,37	380/1/50	1475	3,65	23,1



CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R 22 MBP/MHBP

DIMENSIONI - PESI - ATTACCHI
 DIMENSIONS - WEIGHT - CONNECTIONS
 ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 16.5/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 15.5/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.5L/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.5/A	300 x 480 x 250	21,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.5/A	300 x 480 x 250	22,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.5/A	300 x 510 x 265	26,2	1/2" - 12	1/4" - 6	3/8" FPT
WV 58.5L/A	300 x 510 x 265	34,8	1/2" - 12	3/8" - 10	3/8" FPT
WV 34.5/A	300 x 510 x 265	31,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 100.5L/A	390 x 480 x 350	34,8	1/2" - 12	3/8" - 10	3/8" FPT
TWV 100.5L/A	390 x 480 x 350	34,8	1/2" - 12	3/8" - 10	3/8" FPT
WV 110.5/A	390 x 480 x 350	35,5	1/2" - 12	3/8" - 10	3/8" FPT
TWV 110.5/A	390 x 480 x 350	35,1	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.5/A	390 x 480 x 350	37,0	1/2" - 12	3/8" - 10	3/8" FPT
TWV 120.5/A	390 x 480 x 350	36,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 130.5/A	540 x 450 x 360	38,0	1/2" - 12	3/8" - 10	1/2" FPT
TWV 130.5/A	540 x 450 x 360	37,5	1/2" - 12	3/8" - 10	1/2" FPT
WV 150.5/A	540 x 450 x 360	39,0	1/2" - 12	3/8" - 10	1/2" FPT
TWV 150.5/A	540 x 450 x 360	39,0	1/2" - 12	3/8" - 10	1/2" FPT
WC 16.5/A	300 x 480 x 250	19,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 15.5/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.5L/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.5/A	300 x 480 x 250	20,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.5/A	300 x 480 x 250	21,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.5/A	300 x 510 x 265	25,0	1/2" - 12	1/4" - 6	3/8" FPT
WC 58.5L/A	300 x 510 x 265	33,8	1/2" - 12	3/8" - 10	3/8" FPT
WC 34.5/A	300 x 510 x 265	30,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 100.5L/A	390 x 480 x 350	33,8	1/2" - 12	3/8" - 10	3/8" FPT
WC 110.5/A	390 x 480 x 350	34,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.5/A	390 x 480 x 350	36,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 130.5/A	540 x 450 x 360	37,0	1/2" - 12	3/8" - 10	1/2" FPT
WC 150.5/A	540 x 450 x 360	38,0	1/2" - 12	3/8" - 10	1/2" FPT

