

CON COMPRESSORE L' UNITE' HERMETIQUE
 WITH L' UNITE' HERMETIQUE COMPRESSOR
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

R134a MBP/MHBP

| Modello Model Modell | Resa - Capacity - Leistung (Watt) | | | | | Caratteristiche compressore Compressor characteristics Kompressormerkmale | | | Caratteristiche elettriche Electrical data Elektrische Daten | | | |
|----------------------------|--------------------------------------|------|-------|-------|-------|---|------------|--|--|--|------------|------------|
| | 0°C | -5°C | -10°C | -15°C | -25°C | Modello Model Modell | HP nom. | Cilindrata Displacem. Dampfinhalt (cm³) | Tensione Voltage Spannung | Potenza ass. max Max power absorb. Leistingsaufn. (W) | FLA (A) | LRA (A) |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

| | | | | | | | | | | | |
|------------|------|------|------|------|----------|-----|-------|----------|------|------|------|
| WV 16.11 | 336 | 262 | 199 | 145 | AZ4414Y | 1/6 | 4,00 | 220/1/50 | 142 | 0,83 | 8,1 |
| WV 15.11 | 470 | 376 | 297 | 232 | AZ4419Y | 1/5 | 5,60 | 220/1/50 | 205 | 1,26 | 9,0 |
| WV 14.11L | 622 | 487 | 372 | 276 | AEZ4425Y | 1/4 | 7,55 | 220/1/50 | 230 | 1,41 | 9,0 |
| WV 14.11 | 762 | 603 | 470 | 364 | AEZ4430Y | 1/4 | 8,85 | 220/1/50 | 282 | 1,97 | 10,0 |
| WV 13.11 | 998 | 783 | 604 | 461 | CAE4440Y | 1/3 | 12,05 | 220/1/50 | 363 | 2,47 | 15,0 |
| WV 38.11 | 1219 | 967 | 761 | 599 | CAE4448Y | 3/8 | 14,15 | 220/1/50 | 420 | 2,60 | 17,0 |
| WV 12.11 | 1379 | 1098 | 866 | 681 | CAE4456Y | 1/2 | 16,00 | 220/1/50 | 504 | 3,46 | 19,0 |
| WV 12.11P | 1524 | 1194 | 921 | 705 | CAJ4461Y | 1/2 | 18,30 | 220/1/50 | 502 | 3,12 | 19,0 |
| TWV 12.11P | 1524 | 1194 | 921 | 705 | TAJ4461Y | 1/2 | 18,30 | 380/3/50 | 439 | 0,99 | 9,4 |
| WV 58.11 | 1855 | 1436 | 1084 | 798 | CAJ4476Y | 5/8 | 21,70 | 220/1/50 | 574 | 3,91 | 24,0 |
| WV 34.11 | 2210 | 1695 | 1248 | 869 | CAJ4492Y | 3/4 | 25,95 | 220/1/50 | 637 | 4,37 | 26,0 |
| TWV 34.11 | 2210 | 1695 | 1248 | 869 | TAJ4492Y | 3/4 | 25,95 | 380/3/50 | 601 | 1,35 | 12,6 |
| WV 100.11 | 2952 | 2307 | 1759 | 1307 | CAJ4511Y | 1 | 32,70 | 220/1/50 | 767 | 3,61 | 29,0 |
| TWV 100.11 | 2952 | 2307 | 1759 | 1307 | TAJ4511Y | 1 | 32,70 | 380/3/50 | 764 | 1,60 | 13,0 |
| WV 150.11 | 4376 | 3306 | 2363 | 1543 | FH4518Y | 1,5 | 53,20 | 220/1/50 | 1068 | 5,32 | 46,0 |
| TWV 150.11 | 4376 | 3306 | 2363 | 1543 | TFH4518Y | 1,5 | 53,20 | 380/3/50 | 1051 | 2,49 | 24,0 |
| WV 200.11 | 5793 | 4464 | 3361 | 2479 | FH4525Y | 2 | 74,25 | 220/1/50 | 1460 | 6,72 | 55,0 |
| TWV 200.11 | 5793 | 4464 | 3361 | 2479 | TFH4525Y | 2 | 74,25 | 380/3/50 | 1410 | 2,74 | 24,0 |

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

| | | | | | | | | | | | |
|-----------|------|------|------|------|----------|-----|-------|----------|-----|------|------|
| WC 16.11 | 336 | 262 | 199 | 145 | AZ4414Y | 1/6 | 4,00 | 220/1/50 | 142 | 0,83 | 8,1 |
| WC 15.11 | 470 | 376 | 297 | 232 | AZ4419Y | 1/5 | 5,60 | 220/1/50 | 205 | 1,26 | 9,0 |
| WC 14.11L | 622 | 487 | 372 | 276 | AEZ4425Y | 1/4 | 7,55 | 220/1/50 | 230 | 1,41 | 9,0 |
| WC 14.11 | 762 | 603 | 470 | 364 | AEZ4430Y | 1/4 | 8,85 | 220/1/50 | 282 | 1,97 | 10,0 |
| WC 13.11 | 998 | 783 | 604 | 461 | CAE4440Y | 1/3 | 12,05 | 220/1/50 | 363 | 2,47 | 15,0 |
| WC 38.11 | 1219 | 967 | 761 | 599 | CAE4448Y | 3/8 | 14,15 | 220/1/50 | 420 | 2,60 | 17,0 |
| WC 12.11 | 1379 | 1098 | 866 | 681 | CAE4456Y | 1/2 | 16,00 | 220/1/50 | 504 | 3,46 | 19,0 |
| WC 12.11P | 1524 | 1194 | 921 | 705 | CAJ4461Y | 1/2 | 18,30 | 220/1/50 | 502 | 3,12 | 19,0 |
| WC 58.11 | 1855 | 1436 | 1084 | 798 | CAJ4476Y | 5/8 | 21,70 | 220/1/50 | 574 | 3,91 | 24,0 |
| WC 34.11 | 2210 | 1695 | 1248 | 869 | CAJ4492Y | 3/4 | 25,95 | 220/1/50 | 637 | 4,37 | 26,0 |
| WC 100.11 | 2952 | 2307 | 1759 | 1307 | CAJ4511Y | 1 | 32,70 | 220/1/50 | 767 | 3,61 | 29,0 |



CON COMPRESSORE L' UNITE' HERMETIQUE
 WITH L' UNITE' HERMETIQUE COMPRESSOR
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

R134a MBP/MHBP

DIMENSIONI - PESI - ATTACCHI
 DIMENSIONS - WEIGHT - CONNECTIONS
 ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

| Modello Model Modell | Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm) | Peso Weight Gewichte (kg) | Attacchi - Connections - Anschlüsse | | Attacchi acqua Water inlet Wasseranschluss |
|----------------------------|---|------------------------------------|-------------------------------------|-------------|--|
| | | | Aspirazione | Liquido | |
| | | | Suction | Liquid | |
| | | | Ansaugen | Flüssigkeit | |
| WV 16.11 | 300 x 480 x 250 | 19,5 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 15.11 | 300 x 480 x 250 | 20,6 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 14.11L | 300 x 480 x 250 | 19,8 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 14.11 | 300 x 480 x 250 | 20,0 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 13.11 | 300 x 480 x 250 | 21,8 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 38.11 | 300 x 510 x 275 | 32,5 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WV 12.11 | 300 x 510 x 275 | 33,6 | 1/2" - 12 | 1/4" - 6 | 3/8" FPT |
| WV 12.11P | 390 x 480 x 285 | 33,6 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| TWV 12.11P | 390 x 480 x 285 | 32,6 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WV 58.11 | 390 x 480 x 285 | 33,6 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WV 34.11 | 390 x 480 x 350 | 33,6 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| TWV 34.11 | 390 x 480 x 350 | 34,5 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WV 100.11 | 390 x 480 x 350 | 36,8 | 5/8" - 16 | 3/8" - 10 | 3/8" FPT |
| TWV 100.11 | 390 x 480 x 350 | 34,7 | 5/8" - 16 | 3/8" - 10 | 3/8" FPT |
| WV 150.11 | 540 x 450 x 390 | 39,0 | 5/8" - 16 | 3/8" - 10 | 1/2" FPT |
| TWV 150.11 | 540 x 450 x 390 | 39,0 | 5/8" - 16 | 3/8" - 10 | 1/2" FPT |
| WV 200.11 | 540 x 450 x 390 | 40,5 | 5/8" - 16 | 3/8" - 10 | 1/2" FPT |
| TWV 200.11 | 540 x 450 x 390 | 40,5 | 5/8" - 16 | 3/8" - 10 | 1/2" FPT |
| WC 16.11 | 300 x 480 x 250 | 20,0 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 15.11 | 300 x 480 x 250 | 20,8 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 14.11L | 300 x 480 x 250 | 19,0 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 14.11 | 300 x 480 x 250 | 19,5 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 13.11 | 300 x 480 x 250 | 20,7 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 38.11 | 300 x 510 x 275 | 30,5 | 3/8" - 10 | 1/4" - 6 | 3/8" FPT |
| WC 12.11 | 300 x 510 x 275 | 31,5 | 1/2" - 12 | 1/4" - 6 | 3/8" FPT |
| WC 12.11P | 390 x 480 x 285 | 31,5 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WC 58.11 | 390 x 480 x 285 | 31,9 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WC 34.11 | 390 x 480 x 350 | 31,9 | 1/2" - 12 | 3/8" - 10 | 3/8" FPT |
| WC 100.11 | 390 x 480 x 350 | 34,4 | 5/8" - 16 | 3/8" - 10 | 3/8" FPT |

