

CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R134a MBP/MHBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)				Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	0°C	-5°C	-10°C	-15°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 15.11/A	451	367	297	237	NB6144Z	1/5	6,06	220/1/50	215	1,21	7,5
WV 14.11L/A	573	451	357	293	NE6160Z	1/4	8,00	220/1/50	214	1,43	10,8
WV 14.11/A	678	539	422	329	NE6170Z	1/4	8,79	220/1/50	246	1,51	11,0
WV 13.11/A	927	744	587	458	NE6187Z	1/3	12,10	220/1/50	356	2,31	13,8
WV 12.11/A	1246	974	727	504	T6213Z	1/2	17,40	220/1/50	520	3,34	20,0
WV 58.11/A	1480	1153	890	693	T6215Z	5/8	20,40	220/1/50	535	3,56	21,0
WV 34.11/A	1992	1568	1237	999	NJ6220Z	3/4	25,80	220/1/50	670	4,46	35,0
TWV 34.11/A	1992	1568	1237	999	NJ6220ZX	3/4	25,80	380/3/50	587	1,18	10,0
WV 100.11/A	2810	2334	1935	1614	NJ6226Z	1	34,37	220/1/50	798	5,52	31,0
TWV 100.11/A	2810	2334	1935	1614	NJ6226ZX	1	34,37	380/3/50	798	1,72	13,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 15.11/A	451	367	297	237	NB6144Z	1/5	6,06	220/1/50	215	1,21	7,5
WC 14.11L/A	573	451	357	293	NE6160Z	1/4	8,00	220/1/50	214	1,43	10,8
WC 14.11/A	678	539	422	329	NE6170Z	1/4	8,79	220/1/50	246	1,51	11,0
WC 13.11/A	927	744	587	458	NE6187Z	1/3	12,10	220/1/50	356	2,31	13,8
WC 12.11/A	1246	974	727	504	T6213Z	1/2	17,40	220/1/50	520	3,34	20,0
WC 58.11/A	1480	1153	890	693	T6215Z	5/8	20,40	220/1/50	535	3,56	21,0
WC 34.11/A	1992	1568	1237	999	NJ6220Z	3/4	25,80	220/1/50	670	4,46	35,0
WC 100.11/A	2810	2334	1935	1614	NJ6226Z	1	34,37	220/1/50	798	5,52	31,0



CON COMPRESSORE **EMBRACO - ASPERA**
 WITH **EMBRACO - ASPERA COMPRESSOR**
 MIT **EMBRACO - ASPERA KOMPRESSOR**

R134a MBP/MHBP

DIMENSIONI - PESI - ATTACCHI
DIMENSIONS - WEIGHT - CONNECTIONS
ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 15.11/A	300 x 480 x 250	19,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.11L/A	300 x 480 x 250	19,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 14.11/A	300 x 480 x 250	20,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.11/A	300 x 480 x 250	21,8	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.11/A	300 x 510 x 275	21,8	1/2" - 12	1/4" - 6	3/8" FPT
WV 58.11/A	300 x 510 x 275	28,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 34.11/A	390 x 480 x 350	33,7	1/2" - 12	3/8" - 10	3/8" FPT
TWV 34.11/A	390 x 480 x 350	33,6	1/2" - 12	3/8" - 10	3/8" FPT
WV 100.11/A	390 x 480 x 350	36,8	1/2" - 12	3/8" - 10	3/8" FPT
TWV 100.11/A	390 x 480 x 350	36,8	1/2" - 12	3/8" - 10	3/8" FPT
WC 15.11/A	300 x 480 x 250	18,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.11L/A	300 x 480 x 250	18,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 14.11/A	300 x 480 x 250	19,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.11/A	300 x 480 x 250	20,8	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.11/A	300 x 510 x 275	20,8	1/2" - 12	1/4" - 6	3/8" FPT
WC 58.11/A	300 x 510 x 275	27,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 34.11/A	390 x 480 x 350	32,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 100.11/A	390 x 480 x 350	35,8	1/2" - 12	3/8" - 10	3/8" FPT

