

CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R404A LBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	-10°C	-20°C	-25°C	-30°C	-40°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 14.13	910	552	424	326		AEZ2415Z	1/4	8,10	220/1/50	354	2,14	14,0
WV 13.13	1137	719	545	392		CAE2417Z	1/3	11,30	220/1/50	390	1,87	13,1
WV 38.13	1332	845	656	500		CAE2420Z	3/8	12,50	220/1/50	507	3,09	18,0
WV 12.13	1534	1011	801	621		CAE2424Z	1/2	15,00	220/1/50	590	2,41	17,0
TWV 12.13	1630	991	751	560		TAJ2428Z	1/2	15,20	380/3/50	527	1,06	9,4
WV 34.13	2010	1241	950	717		CAJ2432Z	3/4	18,30	220/1/50	626	2,51	21,0
WV 120.13	2958	1844	1439	1128		CAJ2446Z	1,2	26,15	220/1/50	911	3,73	29,0
TWV 120.13	2958	1844	1439	1128		TAJ2446Z	1,2	26,15	380/3/50	896	1,38	13,0
WV 150.13	3889	2471	1941	1520		CAJ2464Z	1,5	34,45	220/1/50	1220	5,13	38,0
TWV 150.13	3889	2471	1941	1520		TAJ2464Z	1,5	34,45	380/3/50	1215	1,93	16,0
TWV 200.13	5804	3468	2584	1856		TFH2480Z	2	53,20	380/3/50	1721	2,63	23,0
TWV 300.13	8068	4884	3735	2854		TFH2511Z	3	74,25	380/3/50	2059	3,31	28,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 14.13	910	552	424	326		AEZ2415Z	1/4	8,10	220/1/50	354	2,14	14,0
WC13.13	1137	719	545	392		CAE2417Z	1/3	11,30	220/1/50	390	1,87	13,1
WC 38.13	1332	845	656	500		CAE2420Z	3/8	12,50	220/1/50	507	3,09	18,0
WC 12.13	1534	1011	801	621		CAE2424Z	1/2	15,00	220/1/50	590	2,41	17,0
WC 34.13	2010	1241	950	717		CAJ2432Z	3/4	18,30	220/1/50	626	2,51	21,0
WC 120.13	2958	1844	1439	1128		CAJ2446Z	1,2	26,15	220/1/50	911	3,73	29,0
WC 150.13	3889	2471	1941	1520		CAJ2464Z	1,5	34,45	220/1/50	1220	5,13	38,0



CON COMPRESSORE L' UNITE' HERMETIQUE  
 WITH L' UNITE' HERMETIQUE COMPRESSOR  
 MIT L' UNITE' HERMETIQUE KOMPRESSOR

**R404A LBP**

DIMENSIONI - PESI - ATTACCHI  
 DIMENSIONS - WEIGHT - CONNECTIONS  
 ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 14.13	300 x 480 x 250	21,7	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.13	300 x 480 x 250	23,8	3/8" - 10	1/4" - 6	3/8" FPT
WV 38.13	300 x 480 x 250	22,7	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.13	300 x 510 x 275	32,6	3/8" - 10	1/4" - 6	3/8" FPT
TWV 12.13	390 x 480 x 285	32,6	1/2" - 12	1/4" - 6	3/8" FPT
WV 34.13	390 x 480 x 285	33,3	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.13	390 x 480 x 350	34,7	1/2" - 12	3/8" - 10	3/8" FPT
TWV 120.13	390 x 480 x 350	35,7	1/2" - 12	3/8" - 10	3/8" FPT
WV 150.13	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT
TWV 150.13	540 x 450 x 360	37,9	5/8" - 16	3/8" - 10	1/2" FPT
TWV 200.13	540 x 450 x 390	65,5	5/8" - 16	3/8" - 10	1/2" FPT
TWV 300.13	540 x 450 x 390	65,5	5/8" - 16	3/8" - 10	1/2" FPT
WC 14.13	300 x 480 x 250	21,7	3/8" - 10	1/4" - 6	3/8" FPT
WC13.13	300 x 480 x 250	22,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 38.13	300 x 480 x 250	21,7	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.13	300 x 510 x 275	30,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 34.13	390 x 480 x 285	31,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.13	390 x 480 x 350	33,0	1/2" - 12	3/8" - 10	3/8" FPT
WC 150.13	540 x 450 x 360	39,0	5/8" - 16	3/8" - 10	1/2" FPT

