

CON COMPRESSORE EMBRACO - ASPERA
 WITH EMBRACO - ASPERA COMPRESSOR
 MIT EMBRACO - ASPERA KOMPRESSOR

R404A LBP

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	-10°C	-20°C	-25°C	-30°C	-40°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm³)	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 14.13/A	606	384	291	212	87	E2125GK	1/4	8,85	220/1/50	344	2,16	13,8
WV 13.13/A	807	540	425	320	129	E2134GK	1/3	12,00	220/1/50	418	2,48	16,4
WV 12.13/A	1028	615	462	340	165	T2155GK	1/2	14,50	220/1/50	625	3,41	20,0
WV 34.13/A	1211	764	594	453	239	T2168GK	3/4	17,40	220/1/50	647	3,79	18,0
WV 100.13L/A	1339	876	694	537	288	T2178GK	1	20,40	220/1/50	708	3,03	21,0
WV 120.13/A	1830	1194	934	711	382	NJ2192GK	1,2	26,00	220/1/50	950	4,01	26,0
TWV 120.13/A	1830	1194	934	711	382	NJ2192GS	1,2	26,00	380/3/50	1097	1,85	13,0
WV 150.13/A	2414	1610	1263	954	446	NJ2212GK	1,5	34,37	220/1/50	1180	5,39	36,0
TWV 150.13/A	2414	1610	1263	954	446	NJ2212GS	1,5	34,37	380/3/50	1168	1,88	13,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 14.13/A	606	384	291	212	87	E2125GK	1/4	8,85	220/1/50	344	2,16	13,8
WC 13.13/A	807	540	425	320	129	E2134GK	1/3	12,00	220/1/50	418	2,48	16,4
WC 12.13/A	1028	615	462	340	165	T2155GK	1/2	14,50	220/1/50	625	3,41	20,0
WC 34.13/A	1211	764	594	453	239	T2168GK	3/4	17,40	220/1/50	647	3,79	18,0
WC 100.13L/A	1339	876	694	537	288	T2178GK	1	20,40	220/1/50	708	3,03	21,0
WC 120.13/A	1830	1194	934	711	382	NJ2192GK	1,2	26,00	220/1/50	950	4,01	26,0
WC 150.13/A	2414	1610	1263	954	446	NJ2212GK	1,5	34,37	220/1/50	1180	5,39	36,0



CON COMPRESSORE **EMBRACO - ASPERA**
 WITH **EMBRACO - ASPERA** COMPRESSOR
 MIT **EMBRACO - ASPERA** KOMPRESSOR

R404A LBP

DIMENSIONI - PESI - ATTACCHI
DIMENSIONS - WEIGHT - CONNECTIONS
ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 14.13/A	300 x 480 x 250	22,7	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.13/A	300 x 480 x 250	24,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.13/A	300 x 510 x 275	26,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 34.13/A	300 x 510 x 275	27,0	1/2" - 12	1/4" - 6	3/8" FPT
WV 100.13L/A	300 x 510 x 275	28,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.13/A	390 x 480 x 350	35,7	1/2" - 12	3/8" - 10	3/8" FPT
TWV 120.13/A	390 x 480 x 350	35,7	1/2" - 12	3/8" - 10	3/8" FPT
WV 150.13/A	540 x 450 x 360	39,0	1/2" - 12	3/8" - 10	3/8" FPT
TWV 150.13/A	540 x 450 x 360	37,9	1/2" - 12	3/8" - 10	3/8" FPT
WC 14.13/A	300 x 480 x 250	21,7	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.13/A	300 x 480 x 250	23,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.13/A	300 x 510 x 275	25,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 34.13/A	300 x 510 x 275	26,0	1/2" - 12	1/4" - 6	3/8" FPT
WC 100.13L/A	300 x 510 x 275	27,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.13/A	390 x 480 x 350	34,7	1/2" - 12	3/8" - 10	3/8" FPT
WC 150.13/A	540 x 450 x 360	38,0	1/2" - 12	3/8" - 10	3/8" FPT

