

CON COMPRESSORE ACC (ex Electrolux)

WITH ACC (ex Electrolux) COMPRESSOR

MIT ACC (ex Electrolux) KOMPRESSOR

**R404A LBP**

Modello Model Modell	Resa - Capacity - Leistung (Watt)					Caratteristiche compressore Compressor characteristics Kompressormerkmale			Caratteristiche elettriche Electrical data Elektrische Daten			
	-10°C	-20°C	-25°C	-30°C	-40°C	Modello Model Modell	HP nom.	Cilindrata Displacem. Dampfinhalt (cm <sup>3</sup> )	Tensione Voltage Spannung	Potenza ass. max Max power absorb. Leistingsaufn. (W)	FLA (A)	LRA (A)

APPLICAZIONE VALVOLA TERMOSTATICA CON RUBINETTI

APPLICATION OF THERMOSTATIC VALVE WITH SHUT OF VALVES

ANWENDUNG THERMOSTATVENTIL MIT ABSTELLVENTILEN

WV 14.13/E	679	432	<b>333</b>	252	131	ML90FB	1/4	8,80	220/1/50	366	2,20	12,2
WV 13.13/E	935	575	<b>433</b>	315	141	MP12FB	1/3	12,00	220/1/50	462	2,64	14,8
WV 12.13/E	1025	637	<b>485</b>	357	167	MP14FB	1/2	14,00	220/1/50	567	3,26	17,5
WV 34.13/E	1490	877	<b>639</b>	444	165	MR18FB-T	3/4	18,20	220/1/50	605	2,64	18,0
WV 100.13L/E	1771	1067	<b>791</b>	562	228	MR22FB-T	1	21,78	220/1/50	735	3,36	24,0
WV 120.13/E	1890	1312	<b>989</b>	713	296	MS26FB-T	1,2	26,15	220/1/50	884	4,32	30,0
WV 150.13/E	2751	1701	<b>1281</b>	922	381	MS34FB-T	1,5	34,25	220/1/50	1186	3,84	39,0

APPLICAZIONE CAPILLARE CON RUBINETTI

APPLICATION OF CAPILLARY WITH SHUT OFF VALVES

ANWENDUNG KAPILLARROHR MIT ABSTELLVENTILEN

WC 14.13/E	679	432	<b>333</b>	252	131	ML90FB	1/4	8,80	220/1/50	366	2,20	12,2
WC 13.13/E	935	575	<b>433</b>	315	141	MP12FB	1/3	12,00	220/1/50	462	2,64	14,8
WC 12.13/E	1025	637	<b>485</b>	357	167	MP14FB	1/2	14,00	220/1/50	567	3,26	17,5
WC 34.13/E	1490	877	<b>639</b>	444	165	MR18FB-T	3/4	18,20	220/1/50	605	2,64	18,0
WC 100.13L/E	1771	1067	<b>791</b>	562	228	MR22FB-T	1	21,78	220/1/50	735	3,36	24,0
WC 120.13/E	1890	1312	<b>989</b>	713	296	MS26FB-T	1,2	26,15	220/1/50	884	4,32	30,0
WC 150.13/E	2751	1701	<b>1281</b>	922	381	MS34FB-T	1,5	34,25	220/1/50	1186	3,84	39,0



CON COMPRESSORE **ACC** (ex Electrolux)

WITH **ACC** (ex Electrolux) COMPRESSOR

MIT **ACC** (ex Electrolux) KOMPRESSOR

**R404A LBP**

**DIMENSIONI - PESI - ATTACCHI**

**DIMENSIONS - WEIGHT - CONNECTIONS**

**ABMESSUNGEN - GEWICHTE - ANSCHLÜSSE**

Modello Model Modell	Dimensioni - Dimensions - Abmessungen Larghezza x Profondità x Altezza (mm) Width x Depth x Height (mm) Breite x Tiefe x Höhe (mm)	Peso Weight Gewichte (kg)	Attacchi - Connections - Anschlüsse		Attacchi acqua Water inlet Wasseranschluss
			Aspirazione	Liquido	
			Suction	Liquid	
			Ansaugen	Flüssigkeit	
WV 14.13/E	300 x 480 x 250	22,7	3/8" - 10	1/4" - 6	3/8" FPT
WV 13.13/E	300 x 480 x 250	24,0	3/8" - 10	1/4" - 6	3/8" FPT
WV 12.13/E	300 x 510 x 275	26,5	3/8" - 10	1/4" - 6	3/8" FPT
WV 34.13/E	390 x 480 x 275	27,0	1/2" - 12	1/4" - 6	3/8" FPT
WV 100.13L/E	390 x 480 x 275	28,5	1/2" - 12	3/8" - 10	3/8" FPT
WV 120.13/E	390 x 480 x 350	35,8	1/2" - 12	3/8" - 10	3/8" FPT
WV 150.13/E	540 x 450 x 360	39,0	1/2" - 12	3/8" - 10	1/2" FPT
WC 14.13/E	300 x 480 x 250	21,7	3/8" - 10	1/4" - 6	3/8" FPT
WC 13.13/E	300 x 480 x 250	23,0	3/8" - 10	1/4" - 6	3/8" FPT
WC 12.13/E	300 x 510 x 275	25,5	3/8" - 10	1/4" - 6	3/8" FPT
WC 34.13/E	390 x 480 x 275	26,0	1/2" - 12	1/4" - 6	3/8" FPT
WC 100.13L/E	390 x 480 x 275	27,5	1/2" - 12	3/8" - 10	3/8" FPT
WC 120.13/E	390 x 480 x 350	34,7	1/2" - 12	3/8" - 10	3/8" FPT
WC 150.13/E	540 x 450 x 360	38,0	1/2" - 12	3/8" - 10	1/2" FPT

